



CTD Data RV Heincke HE443

Data Processing Report

Contents

1	Introduction	1
2	Workflow	1
3	Cruise details	3
4	Sensor Layout	3
5	Processing	3
6	Results	5

Contact: Gerd Rohardt Alfred-Wegener-Institute Am Handelshafen 12, D-27570 Bremerhaven, GERMANY Mail: info@awi.de

Processing Agency: FIELAX Schleusenstr. 14, D-27568 Bremerhaven, GERMANY Mail: info@fielax.de Ref.: CTD-HE443-report.pdf

Vers.: 1 Date: 2016/04/07 Status: final



1 Introduction

This report describes the processing of CTD raw data acquired by Seabird SBE 911plus CTD on board RV Heincke during expedition HE443.

2 Workflow

The different steps of processing and validation are visualized in Figure 1. The CTD raw data are delivered from Gerd Rohardt (AWI). The station book of the RV Heincke cruise is extracted from the DAVIS SHIP data base (https://dship.awi.de). The first CTD station and cast is processed manually in SBE Data Processing to configure the *.psa Seabird routines Data Conversion, Wild Edit, Bottle Summary, Split, Translate, Cell Thermal Mass, Loop Edit and Bin Average. The Seabird routines are then run in a batch job CTDjob in ManageCTD to process the complete CTD data set. The downcast of each CTD station/cast is used for further processing. In CTDjob the start record and the lowest altimeter point of the downcast is selected. With the Utilities \rightarrow Dship Ebook function of ManageCTD the DAVIS SHIP station book extraction is used for getting the header information of all CTD stations/casts of the cruise. ManageCTD Utilities -> Find Profile function compares station times of the header with the entries in the station book to find out the correct naming of the stations and casts. In CTDheader in ManageCTD the header information of each CTD station/cast is displayed, controlled and corrected if necessary. CTDdespike in ManageCTD is used for a visual check of the data and to erase/interpolate spikes in the data if necessary. Additionally, a sensor pair (Temp1/Sal1 or Temp2/Sal2) is chosen for each station/cast of the RV Heincke cruise in CTDdespike.

ManageCTD *Utilities* \rightarrow *CheckDoubleSensors* controls the quality of temperature and conductivity sensors. For this purpose outliers of too high sensor pair differences could be removed. The data is then converted to spreadsheet format with *dsp2odv* for visualization of the data in Ocean Data View (ODV). The second visual inspection of the CTD data allows a comparison with data from other CTD casts from close-by stations to verify the oxygen sensor data. Therefore, potential reference cruise data is downloaded from PANGAEA (http://www.PANGAEA.de). The reference data is converted to *.mat format. In the ManageCTD Final Processing the CTD data is displayed together with the reference data. Bad data points, sensors or casts are interpolated or erased from the data set and filters are applied if necessary. The processed CTD data are written to text files and imported to PANGAEA (http://www.PANGAEA.de) for publication.




Figure 1: CTD data Processing Workflow



3 Cruise details

Vessel name	RV Heincke
Cruise name	HE443
Cruise start	28.04.2015 Bremerhaven
Cruise end	09.05.2015 Bremerhaven
Cruise duration	12 days
No. of CTD casts	61

4 Sensor Layout

This chapter describes the CTD sensors mounted during this cruise: SBE 911plus CTD (SN: 1015), SBE Instrument Configuration Version 7.23.0.1.

ID	Sensor Name	Serial No.	Calibration Date
55	TemperatureSensor	5354	21-Jan-12
3	ConductivitySensor	2470	15-Nov-13
45	PressureSensor	1015	05-Oct-10
55	TemperatureSensor	5375	21-Jan-12
3	ConductivitySensor	3810	08-Feb-12
0	AltimeterSensor	46466	23-Mar-09
71	WET_LabsCStar	1348DR	13-Oct-2010
20	FluoroWetlabECO_AFL_FL_Sensor	1346	26-Feb-2009
38	OxygenSensor	1597	19-Jun-12

5 Processing

Details of processing procedures and processing parameters are described in *CTD Processing Logbook of RV Heincke* (hdl:10013/epic.47427).

Density Inversions and Manual Validation

Obvius outliers were removed manually. For the visual check density inversions > 0.005 kg/m^3 and > 0.01 kg/m^3 were flagged differently for display but removed automatically. Decisions whether the flagged values were manually removed or not are based on the description in *CTD Processing Logbook of RV Heincke* (hdl:10013/epic.47427).



Sensor Differences




Figure 2: Data accuracy of sensor pairs HE443



6 Results

A complete processing overview for each sensor at each station is summarized in the table in the Appendix (Figure 3).

Double Sensor Check

In Figure 2, the absolute residuals between the two sensorpairs are shown for the measured parameters *Temperature* and *Conductivity* and the derived parameter *Salinity*. Measurements in shallow water depths < 15 m (blue crosses) and gradients between two datapoints exceeding a defined threshold (red crosses) were omitted for accuracy calculation.

	Accuracy	Measurements re-	Remaining measure-
		moved	ments
Parameter	given by manufacturer	Surface 0-15m + gradi-	within accuracy specifi-
		ent filter	cations
Temperature	$\pm 0.001^{\circ}C$	63.92%	24.67%
Conductivity	$\pm 0.003 mS/cm$	52.95%	77.06%
Salinity	$\pm 0.0015 PSU$	55.02%	5.42%

Comments

- 61 CTD/RO "on ground" entries in DShip station book
- 61 CTD raw data sets delivered
- 1 DShip station book entry without raw data (12-1)
- 1 delivered CTD raw data set without DShip station book entry (65-2)
- 1 CTD data set is a failed cast (65-1; data deleted)
- 60 CTD casts processed and uploaded
- of these 60 processed CTD casts:
 - 13 oxygen profiles deleted (spiky and not matching to reference casts)
 - 344 data points interpolated
 - 51 data points erased



Result files

Text File (HE443_phys_oce.tab):

Column separator	Tabulator "\t"
Column 1	Event label
Column 2	Date/Time of event
Column 3	Latitude of event
Column 4	Longitude of event
Column 5	Elevation of event
Column 6	DEPTH, water
Column 7	Pressure, water
Column 8	Temperature, water
Column 9	Conductivity
Column 10	Salinity
Column 11	Temperature, water, potential
Column 12	Density, sigma-theta (0)
Column 13	Oxygen
Column 14	Oxygen, saturation
Column 15	Attenuation, optical beam transmission
Column 16	Fluorometer
Column 17	Number of observations

The format is a plain text (tab-delimited values) file.

Processing Report (CTD-HE443-report.pdf):

This PDF document.

							datafiele 12-1 belongs to stationbook 12-3 entry (53									tationbook entry 24-1;																													data not linear, second data set ntry see below; cast data	entry for second cast 65-2, this is the	oxygen deleted	to stationhock antra 60.2. oversee							
Comments		no bti file oxvgen deleted	0			no data	datafiele 12-1 belongs to	m water deptn)	no btl file							datafile 23-1 belongs to s	oxygen deleted oxygen deleted																		oxygen deleted	uxygen ueleteu								oxygen deleted	oxygen deleted no btl file; Altimeter data for this stationbook entry deleted	no stationbook entry for	data used for 65-1 entry;	oxygen deleted data 60.1 halonor to stat	deleted			oxygen deleted	oxygen deleted oxygen deleted	UAYBerr merene	
		0.T	~0.9	-1.6 ~15	~1.4	/T_	r ž	/1_~	~1.7	~1.3	~1.5	~1.4	*11 *1	~1.0	~1.3			~1.4	~2.1	~2.0	~1.8	~1.7	~1:8	0.5	~ 1	~1.9	~1.6	~1.5	~1.8	4.L~	- 1 V	~1.2	~1.0	~1.1		C C~	~2.1	~1.6	~1.6	~1.7	~ 1	~2.0	~1.8							~2.0	~0.8			~1.6	
referenc	dist. (km)	cT.0	0.92	2.29	51	68./	ł	9.36	6.94	1.72	1.94	10.31	25.61	42.26	67.99	10.00	102.08	2.07	4.4	.46	.18	2.94	6.	4	CP ()	20.03	10.69	3.54	3.83	10.26	14 77	25.39	42.14	58.57	80.84	0C'TO	36	2	11	2.46	3.1/ 9.68	22.63	20.28	10.76	/c.s		3.96	1.94	2.59	.73	.76	1.75	19	.38	
	cruise/sss-cc d	1 7		1E404/32-1 2	_	1-60/h0-T		HE404/33-1 1 HE404/09-1 9	E404/26-1 6	-		E404/27-1 1				0 1 2 1 0 2 0		E404/24-1 2	HE404/11-1 4	404/20-1 0	-	E404/31-1 2	15-1		E404/12-1 9	_	-	E404/32-1 3		E404/26-1 1 E404/44-1 1		4		17-1	E370/17-1 8	T 1-/1/0/c	404/20-1 0	404/13-1 0			E404/1/-1 3		E404/21-1 2	-	16404/32-1 3			HE3/0/42-2 1	HE404/07-1	HE404/31-1 7	E370/42-2 2	E404/07-1 1		09-1 1	
H	erased cru	비민	0 HE	9 9			-	비보	0 HE	H 0	민	9		Ξ	9 H	-		5	9 1 1 1	0 HE	<u> 또</u>	보 0	9 5			H H	9 1 1	H 0	분 8		1	비보	9 HE	9 1	99		H H	비	2 HE	4 4		2 H	5 HE	16 HE	2 112	┝	9	₽	0 HE	9 HE	1 HE	9 H		: 또 이 또 이 또	5
	interp era	~ ~	9	5	n n 1	^ 0		^ ^	1 50	•	12	۲ נו	• •	0	•		0 4	6	•	•	6	••	5	•	• •		∞	•	7	5 5		4	5	9	11	4 4	- 5	•	m	۳ '	~ ~	4	m	14	-		4	•	9	15	15	m ș	a -	10	344
				+				+			+	+	╀						\vdash			+		+	+	+				+	╀	┝	\square	+			+	H	+	+	+	-	-1												9
0xV	interp erased						•	-	1		2	2	-				╞	t			1		-	•	-		1		+		4		1	1						•	-			+			╡	+		1	_	╈	t		23
Fluor	interp erased	2	1					_	1		2	2	-				-	1 1			1		1	,	-		1		1		4		1		m +	-					-	-	1	2 4	-		-			1			4		38 9
		+		_	++			+			+	_	╀	╞			+					_		+	+					+	╀	\vdash	\square	_	+	+		Η	_	+	+		1	4			+	+		Η		+	╞	╞	6
Trans	interp erased	2	'				Ŧ	-	1		2	2	-				+	-				+		+	-		1		-		4	\vdash	1	-	m +	-			-		-	+		2	-		1			1		-	4	-	38
Π	erased	t	Ħ	1				t			1		t	t			T	-						╈	t	T				T	t	T	Π	1	╈	t	T	Π		2	╎	-	1	4	-	r	╡	t		Π	7	T	T	t	14
Sal	interp ei	7	ŝ			7	,	-	-		m	s r	7 -			ſ	o +	5				S	~	+	1	t	2				4	2		4	m +	- ~	n w		m	9	7 0	5	1	m	7	F		m	7	9	6	mu	n	t	129
Π	erased	T						T			1		t	t			T	-						╈	t					T	t	T			╈	T				2		-	1	4,	-		1	T				T	T	t	13
Temp	nterp e	7	m			'n	•		-		m	2 0	0 F			•	7	-			S	m	~		7	t	m				4	2	-	m	- m		5		1	~ ~	7	2	2	~ (n		-	m	2	9	9	-		1	116
2	ar ,	7	-		101	1	ſ	7	2	1	7		-		1		7 ~	2	-	1	-	2		-	- ~		2	1	2	7		• ••	1	-		7 0	2	1	2		7 0	-	1	5	7	r	-	-	1	2	1		-	-	Γ
	ame	1	4-1.*	-	0-1.*		-	13-1.*	4-1.*	16-1.*	7-1.*	8-1.*	-TT	21-1.*	22-1.*	* • • •	5-1.*	7-1.*	8-1.*	9-1.*	0-1.*	1-1.*	2-1.*			e-1:*	7-1.*	8-1.*	1-1.*	43-1.*	*	e-1:*	t7-1.*	48-1.*	0-1-	4-1 *	2-1:*	6-1.*	7-1.*	8-1.*		1-1.	52-1.*	3-1.*	• T- 1 0		65-2.*	66-1.*	69-1.*	1-1.*	5-1.*	70.1.*	1.	5 1.*	
Depth F		10.6		18.6	30.1	8.8		15.4	22.1	50.4 1	41.3	35.8	c./o	34.1	34.3 2		_	36.6 2	19.7 2	11.9 2	19.8	20.9	16.7	/17	+	10.5	17.0 3	26.7 3	10.0	39.4 4	0.1 8	36.0 4	35.8 4	34.4	37.5	6 8 U	12.4 5	22.8 5	22.5 5	16.0	1176	9.6	11.5 6	21.4 6	13.7 6			41.3 6	38.1 6	19.4 7	19.3 7	8.2	0.1	38.4 8	
	1	8° 5.19° E	ш	7° 58.86' E	7° 58.13' E	7° 54.20' E		7° 55.47' F	7° 50.08' E		_	7° 34.17' E	7° 11.40' E			L 100 F 00		ш	8° 4.72' E	8° 13.86' E	8° 19.29' E	8° 24.22' E	8° 31.83' E	8° 41.34' E	8° 73 48' F	8° 18.17' E	8° 8.63' E	8° 2.30' E	7° 56.28' E	7° 3/ 35' E	7° 73 20' F	7° 11.79' E	ш	ш	6° 8.10' E	8° 5 21' F	8° 13.66' E	8° 18.86' E	8° 24.04' E	8° 31.34' E	8° 19 04' F	8° 23.19' E		_	8- 2.46' E	1 01-00	ш	/~ 53.0/* E	ш		7° 52.14' E	5 54° 6.09' N 7° 58.16' E 2	7° 52.11' F	7° 56.53' E	
Ē					2' N			zz	_		_	_						+	3.27' N	2, N	36' N	87' N	N 10	z	_						_	_		_	zz		94' N	55' N	92' N	06' N	N 93.64 N		07' N				_	-			1. N	N 10.6	N 10	N	
Position				54° 10.	54° 5.1		ŝ	54°					1 54° 16 21' N				9 54° 46.78' N		7 54° 3.2	0 54° 1.6	5 53° 59.36' N		8 53° 58.0	0 53° 53.7	2 24° 13 49' N			8 54° 10.91' N	7 54° 10.96' N	3 54° 10.92' N 5 54° 0 02' N					13 54° 39.62' 41 54° 46 54'		8 54° 1.9	0 53° 59.5	28	1 53° 58.0	8 54° 6 66' N				N .58.11 .08.1			9 54° 9.06'N	13:10 54° 5.11' N	0 54° 17.24' N	4 54° 7.9	5 54° 6.0	4 54° 12.3	4 54° 9.2	
Time	-	14:04	+ +	11:19 5 7:07		 11:43 12:22 		13:55 C	15 8:18	· · ·	_	5 7:47			IS 13:34	10.07		+	15 7:2	L5 8:2	2	5 9:22	10:0	11:0	14-29		15:40	16:18	17:2	5 7:33		-		14:	5 16:1	F 7 5	5 10:2	IS 11:1	5 11:3	5 12:1	15.0	16:18	IS 16:46		18:41			19:39			I5 14:5	L5 6:35		IS 6:14	
Date	-	28.04.2015		29.04.2015	100		_	30.04.2015	01.05.2015	01		02.05.2015				01.01.1015		-	03.05.2015	-	-	03.	8	88	CTU2.CU.SU 03.05.2015	8		03.05.2015		04.05.2015					04.05.201	05.05.201	05.05.201	05.05.201	05.	05	05.05.2015	05.05	05.05.2015		5105.20.20	03-00-00	_	05.05.2015	06.05.2015		07.05.2	08.05.2015	08.05.201	09.05.2015	
		CTD/RO	CTD/RO	CTD/RO		CTD/RO	00/0L0		CTD/RO	U.			CTD/RO		CTD/RO		CTD/RO		CTD/RO	CTD/RO		5	CTD/RO	CTD/RO	CTD/RO			CTD/RO	CTD/RO	CTD/RO		CTD/RO			CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO			CTD/RO		CTD/RO			CID/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO		CTD/RO	
Station	HE443/	1-TOOO		0006-1		1-7100		1-2100	0014-1	0016-1	0017-1	0018-1	1-6100	0021-1	0022-1	• • • • • • • • • • • • • • • • • • • •	0025-1	0027-1	0028-1	0029-1	0030-1	0031-1	0032-1	0033-1	1-4-00	0036-1	0037-1	0038-1	0041-1	0043-1	0045-1	0046-1	0047-1	0048-1	0050-1	1-TC00	0055-1	0056-1	0057-1	0058-1	1-6500	0061-1	0062-1	0063-1	1-4900	1	0065-1	0066-1	0069-3	0071-1	0075-1	0076-1			

Figure 3: CTD data Processing Summary HE443






Figure 4: ODV Screenshot of HE443 CTD data Page 8 of 8