



CTD Data RV Heincke HE461

Data Processing Report

Contents

1	Introduction	1
2	Workflow	1
3	Cruise details	3
4	Sensor Layout	3
5	Processing	3
6	Results	5

Contact:			
Gerd Rohardt			
Alfred-Wegener-Institute			
Am Handelshafen 12, D-27570 Bremerhaven, GERMANY			
Mail: info@awi.de			
Processing Agency:			
FIELAX			
Schleusenstr. 14, D-27568 Bremerhaven, GERMANY			
Mail: info@fielax.de			
Ref.: CTD-HE461-report.pdf	Vers.: 1	Date: 2016/07/27	Status: final



1 Introduction

This report describes the processing of CTD raw data acquired by Seabird SBE 911plus CTD on board RV Heincke during expedition HE461.

2 Workflow

The different steps of processing and validation are visualized in Figure 1. The CTD raw data are delivered from Gerd Rohardt (AWI). The station book of the RV Heincke cruise is extracted from the DAVIS SHIP data base (https://dship.awi.de). The first CTD station and cast is processed manually in SBE Data Processing to configure the *.psa Seabird routines Data Conversion, Wild Edit, Bottle Summary, Split, Translate, Cell Thermal Mass, Loop Edit and Bin Average. The Seabird routines are then run in a batch job CTDjob in ManageCTD to process the complete CTD data set. The downcast of each CTD station/cast is used for further processing. In CTDjob the start record and the lowest altimeter point of the downcast is selected. With the Utilities \rightarrow Dship Ebook function of ManageCTD the DAVIS SHIP station book extraction is used for getting the header information of all CTD stations/casts of the cruise. ManageCTD Utilities -> Find Profile function compares station times of the header with the entries in the station book to find out the correct naming of the stations and casts. In CTDheader in ManageCTD the header information of each CTD station/cast is displayed, controlled and corrected if necessary. CTDdespike in ManageCTD is used for a visual check of the data and to erase/interpolate spikes in the data if necessary. Additionally, a sensor pair (Temp1/Sal1 or Temp2/Sal2) is chosen for each station/cast of the RV Heincke cruise in CTDdespike.

ManageCTD *Utilities* \rightarrow *CheckDoubleSensors* controls the quality of temperature and conductivity sensors. For this purpose outliers of too high sensor pair differences could be removed. The data is then converted to spreadsheet format with *dsp2odv* for visualization of the data in Ocean Data View (ODV). The second visual inspection of the CTD data allows a comparison with data from other CTD casts from close-by stations to verify the oxygen sensor data. Therefore, potential reference cruise data is downloaded from PANGAEA (http://www.PANGAEA.de). The reference data is converted to *.mat format. In the ManageCTD Final Processing the CTD data is displayed together with the reference data. Bad data points, sensors or casts are interpolated or erased from the data set and filters are applied if necessary. The processed CTD data are written to text files and imported to PANGAEA (http://www.PANGAEA.de) for publication.




Figure 1: CTD data Processing Workflow



3 Cruise details

Vessel name	RV Heincke
Cruise name	HE461
Cruise start	15.04.2016 Bremerhaven
Cruise end	26.04.2016 Bremerhaven
Cruise duration	12 days
No. of CTD casts	58

4 Sensor Layout

This chapter describes the CTD sensors mounted during this cruise: SBE 911plus CTD (SN: 1015), SBE Instrument Configuration Version 7.23.0.1.

ID	Sensor Name	Serial No.	Calibration Date
55	TemperatureSensor	5354	19-Jan-16
3	ConductivitySensor	3810	08-Dec-15
45	PressureSensor	1015	05-Oct-10
55	TemperatureSensor	5375	19-Jan-16
3	ConductivitySensor	2470	08-Dec-15
0	AltimeterSensor	46466	23-Mar-09
71	WET_LabsCStar	1348DR	28-Jan-2016
20	FluoroWetlabECO_AFL_FL_Sensor	1365	15-Jan-2016
38	OxygenSensor	1597	22-Dec-15

5 Processing

Details of processing procedures and processing parameters are described in *CTD Processing Log*book of *RV Heincke* (hdl:10013/epic.47427).

Density Inversions and Manual Validation

Obvius outliers were removed manually. For the visual check density inversions > 0.005 kg/m^3 and > 0.01 kg/m^3 were flagged differently for display but removed automatically. Decisions whether the flagged values were manually removed or not are based on the description in *CTD Processing Logbook of RV Heincke* (hdl:10013/epic.47427).



Sensor Differences




Figure 2: Data accuracy of sensor pairs HE461



6 Results

A complete processing overview for each sensor at each station is summarized in the table in the Appendix (Figure 3).

Double Sensor Check

In Figure 2, the absolute residuals between the two sensorpairs are shown for the measured parameters *Temperature* and *Conductivity* and the derived parameter *Salinity*. Measurements in shallow water depths < 15 m (blue crosses) and gradients between two datapoints exceeding a defined threshold (red crosses) were omitted for accuracy calculation.

	Accuracy	Measurements re-	Remaining measure-
		moved	ments
Parameter	given by manufacturer	Surface 0-15m + gradi-	within accuracy specifi-
		ent filter	cations
Temperature	$\pm 0.001^{\circ}C$	59.60%	71.56%
Conductivity	$\pm 0.003 mS/cm$	59.75%	70.57%
Salinity	$\pm 0.0015 PSU$	61.97%	50.43%

Comments

- 58 CTD/RO "on ground" entries in DShip station book
- 58 CTD raw data sets delivered
- 1 CTD cast was invalid or test (999.hex)
- 0 CTD cast was made twice on a station
- 41 CTD casts had a wrong filename
- 57 CTD casts processed and uploaded (station HE461/0006-1 missing)
- of these 57 processed CTD casts:
 - 21 oxygen profiles deleted (spiky and not matching to reference casts)
 - 178 data points interpolated
 - 2009 data points erased



Result files

Text File (HE461_phys_oce.tab):

Column separator	Tabulator "\t"
Column 1	Event label
Column 2	Date/Time of event
Column 3	Latitude of event
Column 4	Longitude of event
Column 5	Elevation of event
Column 6	DEPTH, water
Column 7	Pressure, water
Column 8	Temperature, water
Column 9	Conductivity
Column 10	Salinity
Column 11	Temperature, water, potential
Column 12	Density, sigma-theta (0)
Column 13	Oxygen
Column 14	Oxygen, saturation
Column 15	Attenuation, optical beam transmission
Column 16	Fluorometer
Column 17	Number of observations

The format is a plain text (tab-delimited values) file.

Processing Report (CTD-HE461-report.pdf):

This PDF document.

	inter	Sal interp erased	Sensor Temp Sal Pair interp erased interp
			17 1-1.* 1
$ \left \begin{array}{c c c c c c c c c c c c c c c c c c c $			30 3-1.* 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	1	1	31 4-2.* 1 1 1
$ \left \begin{array}{c c c c c c c c c c c c c c c c c c c $			
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$			217-1.* 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	2 2		2
$ \left \begin{array}{c c c c c c c c c c c c c c c c c c c $			5112-1.* 2
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$			1414-1.* 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	2 1		1 1 2
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	2 2		2
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	1	4	
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	1	1 1	Elbe4.* 1 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$		1	20 Elbe5.* 1 1 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	1 1		Elbe6.* 1 1 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	1	1 1	1 1 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$			17 Elbe8.* 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$			39 P8-2.* 2
2 0 HEA43/A11 0.33 0.8 1 100 5 100 HE399/02-1 11.37 0.8 35 0 35 HE399/02-1 12.60 11 1 1 25 0 25 HE443/35-1 0.06 0.4 1 25 0 25 HE443/35-1 0.06 0.4 1 120 0 132 HE443/35-1 0.06 0.4 1 140 132 HE443/35-1 0.05 0.4 0.4 1 140 132 HE443/45-1 0.26 1.0 0.1 1 140 1 140 140 140 0.5 0.7 0.7 1 1 202 HE443/45-1 0.05 0.5 0.5 0.7 1 1 1 202 HE443/45-1 0.78 0.5 0.5 1 1 20 31 1.43 0.7 0.			37 P8-4.* 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	2		Eider-1.* 2
35 0 35 HE39/20-1 12.60 11 25 0 25 HE443/35-1 0.06 0.4 0 1 25 0 25 HE443/35-1 0.06 0.4 0 1 122 0 132 HE443/35-1 0.26 1.0 0 1 132 0 132 HE443/45-1 0.21 1.1 0.7 0 1 140 1 140 HE443/45-1 0.21 1.1 0.7<	1	1 1	Eider-2.* 1 1
25 0 25 HE443/35-1 0.06 0.4 1 20 0 HE443/35-1 0.28 0.4 1 132 0 HE443/43-1 0.12 0.4 1 132 0 132 HE443/43-1 0.26 0.4 1 140 0 1 140 HE443/47-1 0.21 1.1 1 140 0 140 HE443/42-1 0.26 1.0 1 140 0 140 HE443/52-1 0.21 1.1 1 1202 7 202 HE443/52-1 0.78 0.6 2 0 32 HE443/52-1 0.778 0.6 0.5 2 0 33 HE443/55-1 0.705 0.5 0.5 1 42 5 42 HE443/55-1 0.65 0.5 1 1 42 5 42 HE443/55-1 0.50 0.5 1			22 Eider-3.* 1
0 0 HE443/35-1 0.28 1 132 0 1443/43-1 0.12 1 132 0 132 HE443/47-1 0.26 1.0 1 140 11 140 146 HE443/47-1 0.21 1.1 1 140 0 140 HE443/47-1 0.21 1.1 1 140 0 140 HE443/47-1 0.21 0.7 1 1202 7 202 HE443/47-1 0.31 0.7 1 202 7 202 HE443/42-1 0.17 0.5 2 0 32 HE443/42-1 0.778 0.6 32 0 33 HE443/56-1 0.50 0.5 1 42 5 42 HE443/56-1 0.6 0.5 1 1 2 1 0.50 0.5 0.5 0.4 1 42 5 42 HE443/56-1			13 Eider-4.* 1
1 8 1 Head3/43:1 0.12 10 1 132 0 132 HE443/47-1 0.26 1.0 1 140 11 140 14 140 13 140 1 140 1 140 140 140 141 0.7 1 140 0 140 HE443/45-1 0.31 0.7 1 1202 7 202 HE443/45-1 0.31 0.7 1 202 2 22 HE443/45-1 0.31 0.7 1 202 32 HE443/55-1 0.50 0.5 32 0 53 HE443/55-1 0.50 0.5 1 42 5 42 HE443/55-1 0.3 0.3 1 1 42 5 42 HE443/55-1 0.3 0.3 1 1 42 5 42 HE443/55-1 0.3 0.3			1 Eider-5.* 1
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	2	2 2	
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$			34 P8-7.* 1
140 0 140 HE443/45-1 0.31 0.7 1 202 7 202 HE443/82-1 1.19 0.5 2 0 0 HE443/82-1 1.19 0.5 32 0 32 HE443/29-1 0.78 0.6 32 0 32 HE443/56-1 0.50 0.5 1 42 5 42 HE443/35-1 0.50 0.5 1 42 5 42 HE443/35-1 0.11 0.3 32 HE443/35-1 0.50 0.11 0.5 0.5 32 HE443/35-1 0.17 0.4 0.4 32 9 42 HE443/35-1 0.4 0.4 32 9 6 HE443/35-1 0.18 0.4 0.4 32 9 0 HE443/55-1 0.18 0.4 0.4	1	1 1	1 1
1 202 7 202 HE443/82.1 1.19 0.5 32 0 32 HE443/25.1 0.48 0.5 32 0 32 HE443/25.1 0.78 0.6 33 0 33 HE443/55.1 0.50 0.5 1 42 5 42 HE443/55.1 0.50 0.5 1 42 5 42 HE443/35.1 0.11 0.3 32 0 32 HE443/35.1 0.27 0.3 0 32 0 32 HE443/35.1 0.47 0.4 0.4 32 0 32 HE443/35.1 0.47 0.4 0.4 32 0 32 HE443/35.1 0.18 0.4 0.4 4 0 HE443/55.1 0.18 0.4 0.4 0.4			P8-5.* 1
0 0 HE443/28-1 0.48 0.6	m	1 3	47 Elbe1_2.* 1 1 1 3
32 0 32 HE443/29-1 0.78 0.6 53 0 53 HE443/56-1 0.50 0.5 1 2 5 3 HE443/58-1 0.50 0.5 1 42 5 42 HE443/58-1 0.27 0.3 1 42 5 42 HE443/58-1 0.27 0.3 1 32 0 32 HE443/58-1 0.14 0.4 1 32 0 32 HE443/58-1 0.18 0.4 1 0 32 HE443/58-1 0.18 0.4 0.4			19 Elbe3_2.* 1
53 0 53 HE443/56-1 0.50 0.55 1 42 5 42 HE443/58-1 0.11 0.3 1 42 5 42 HE443/58-1 0.27 0.3 32 0 32 HE443/58-1 0.17 0.3 8 0 HE443/55-1 0.18 0.4 0.4 1 0 HE443/55-1 0.18 0.4 0.4			12 Elbe4_2.* 1
0 0 HE443/31-1 0.11 1 42 5 42 HE443/55-1 0.27 0.3 32 0 32 HE443/55-1 0.27 0.3 0.4 32 0 32 HE443/55-1 0.18 0.4 0.4 8 0 HE443/25-1 0.18 0.4 0.4 0.4 1 0 HE443/57-1 0.18 0.4 0.4 0.4			19 Elbe5_2.* 2
1 42 5 42 HE443/58-1 0.27 0.3 32 0 32 HE443/33-1 1.47 0.4 8 0 HE443/25-1 0.18 0.4 1 0 HE443/55-1 0.18 0.4			19 Elbe6_2.* 1
32 0 32 HE443/33-1 1.47 0.4 8 0 HE443/25-1 0.18 1 0 1 0 HE443/50-1 0.08 1 1 1	1	1	13 Elbe7_2.* 1 1 1 1
8 0 HE443/25-1 0.18 1 0 HE443/50-1 0.08			13 Elbe8_2.* 1
HE443/50-1 0.08	2	2 2	
T_00/0111	1	1	38 P8-9 2.* 1 1 1

		isy	noisy, oxygen	isy	Conductivity 2 wrong, O2 very noisy, oxygen deleted	Conductivity 2 wrong, O2 very noisy, oxygen deleted	Conductivity 2 wrong, O2 very noisy, oxygen deleted	isy > 8 m	isy > 9 m	02 very noisy, oxygen deleted	02 very noisy, oxygen deleted	isy > 8 m	isy > 16 m	22 very noisy, oxygen deleted	22 very noisy, oxygen deleted	02 very noisy, oxygen deleted	02 very noisy, oxygen deleted	isy	isy	filename doesn't match	station name, U2 very noisy > 14 m	isy > 12 m	isy > 16 m	
Commonte		02 very noisy	O2 very noi deleted	O2 very noisy	Conductivit very noisy,	Conductivit very noisy,	Conductivit very noisy,	02 very noisy > 8 m	O2 very noisy > 9 m	O2 very no deleted	O2 very no deleted	02 very noisy > 8 m	O2 very noisy > 16 m	02 very noi deleted	O2 very no deleted	O2 very noi deleted	02 very noi deleted	02 very noisy	02 very noisy	filename do	station name noisy > 14 m	O2 very noisy > 12 m	02 very noisy > 16 m	
e) Offset	1.1		1.1				0.2	0.3			6.0	0.6					0.6	0.3		0.4	0.4	0.3	
Oxygen reference	dist. (km	0.08	0.19	0.20	0.32	0.40	0.29	0.25	0.03	0.17	0.06	11.85	3.35	0.45	11.53	3.98	0.32	11.30	1.06		1.06	1.03	1.02	
Oxygen	cruise/sss-cc dist. (km) Offset	HE443/22-1	HE443/47-1	HE443/20-1	HE443/45-1	HE443/18-1	HE443/43-1	HE443/35-1	HE443/36-1	HE443/37-1	HE443/64-1	HE399/02-1	HE399/02-1	HE443/76-1	HE443/14-1	HE443/18-1	HE443/03-1	HE399/02-1	HE443/38-1		HE443/38-1	HE443/38-1	HE443/38-1	
te		145 +	0	154	0	0	0	20 +	18	0	0	48 +	75 +	0	0	0	0	75 +	111 +		71	78 +	82	2009
complete	interp erased	•	0	7	8	0	12	0	•	4	H	0	0	0	'n	-s	4	2	6		0	0	4	178
۲	erased ir	145		154				20	18			48	75					75	111		71	78	82	2004
Оху	interp e			1														H	1					Ř
Chloro																								ſ
Chlo	interp erased			3			9								1	1	1	1	1					37
Trans	interp erased			1			2								1	1	1	1	1					25 1
Sal	interp erased ii			1	5		2			2	1				2	2	1	1	m				2	44
Temp	erased			1	3		2			2					1	1	1	1	m				2	34
	interp		-	1	1	1	1	1	2	2	2	2	2	2		-	F1	5	1		1	1	1	
Sensor	pair	\vdash						*.	*.	2.*	*.	2.*												
cilo		35 P8-8_2.*	35 P8-7_2.*	36 P8-6_2.*	P8-5_2.*	35 P8-4_2.*	40 P8-2_2.*	8 Eider5 2.*	10 Eider4_2.*	17 Eider3_2	28 Eider2_2.*		31 57-1.*	30 59-1.*	25 61-1.*	36 62-2.*	53 63-1.*	21 74-1.*	28 76-1.*		27 77-1.*	28 76-3.*	25 76-4.*	
£	Ξ	35 F	35 P	36 F	37 F	35 F	40	8	10	17	28 E	14 E	315	30	25 6	366	53 6	217	287		27	28	25 7	
Position	Longitude	006° 31.46' E	006° 53.86' E	007° 11.5' E	007° 22.96' E	007° 33.84' E	007° 47.33' E	008° 23.35' E	008° 18.2' E	008° 8.57' E	008° 2.48' E	007° 56.57' E	007° 57.8' E	007° 57.8' E	007° 41.61' E	007° 35.52' E	007° 53.49' E	008° 4.17' E	008° 1.51' E		008° 1.48' E	008° 1.54' E	008° 1.53' E	
	Latitude	9:05 54° 31.09' N	21.04.2016 10:42 54° 22.71' N	21.04.2016 12:08 54° 16.12' N			21.04.2016 15:21 54° 11.04' N			6:00 54° 12.35' N		7:15 54° 10.97' N		6:42 54° 6.21' N	23.04.2016 11:06 54° 17.01' N	23.04.2016 13:20 54° 10.97' N	6:29 54° 8.08' N		9:00 54° 10.57' N		9:15 54° 10.59' N	9:38 54° 10.57' N		
T Imo			10:42 5	12:08 5	13:08 5	14:16 5	15:21 5	17:47 5	18:16 5						11:06 5	13:20 5								
0.40		21.04.2016	21.04.2016	21.04.2016	21.04.2016 13:08 54° 15' N	21.04.2016 14:16 54° 9.07' N	21.04.2016	21.04.2016	21.04.2016 18:16 54° 14' N	22.04.2016	22.04.2016	22.04.2016	22.04.2016	23.04.2016	23.04.2016	23.04.2016	24.04.2016	25.04.2016	25.04.2016		25.04.2016	25.04.2016	25.04.2016	
Gear	Abbr.	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	TD/RO	CTD/RO	CTD/RO	CTD/RO	TD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO	CTD/RO		CTD/RO	CTD/RO	CTD/RO	
	HE461/ A	0046-1 C	0047-1 C	0048-1 C	0049-1 C	0050-1 C	0051-1 C	0052-1 C		0054-1 C	0055-1 C	1		0059-1 C	0061-1 C	0062-1 C	0063-1 C				0076-2 C	0076-3 C	0076-4 C	

Figure 4: CTD data Processing Summary HE461 (continuation)
Page 8 of 9






Figure 5: ODV Screenshot of HE461 CTD data Page 9 of 9