



# Surface T/S Data RV Polarstern PS109 (ARK-XXXI/4)

# **Data Processing Report**

## **Contents**

4	Appendix	5
3	Processing Report	2
2	Sensor Details	1
1	Introduction	1

Contact:

Gerd Rohardt

Alfred-Wegener-Institute

Am Handelshafen 12, D-27570 Bremerhaven, GERMANY

Mail: info@awi.de

Processing Agency:

**FIELAX** 

Schleusenstr. 14, D-27568 Bremerhaven, GERMANY

Mail: info@fielax.de



# 1 Introduction

This report describes the processing of raw data acquired by the thermosalinographs on board RV Polarstern during expedition PS109 to receive cleaned up and corrected salinity data. Detailed description of the processing of the data and the workflow is given in the general report "General Processing Report of Surface T/S Data RV Polarstern Cruises PS106, PS107, PS108 and PS109".

#### Cruise details

Vessel name: RV Polarstern

**Cruise name:** PS109 (ARK-XXXI/4)

Cruise start: 2017-09-16
Cruise end: 2017-10-14
Cruise duration: 28 days

Working area: Northeast Greenland Shelf

#### 2 Sensor Details

Following sensors were installed during cruise PS109. Only data from **TSG1** are uploaded to PAN-GAEA for cruise PS109 and are furthermore considered in this report (for reasoning see General Processing Report).

	TSG1	TSG2
Serial number	SBE21-3191	SBE21-3271
Installation	2016-11-19	2017-06-23
Deinstallation	2017-10-11	2017-10-11
Days installed	326	110
External temperature sensor	SBE38-110	SBE38-119



# 3 Processing Report

#### **Database Extraction**

Data source	DSHIP database (dship.awi.de)
Start of raw file	2017-09-12T04:00:00
End of raw file	2017-10-14T05:59:59
Number of lines in hexadecimal raw	2772000
file	
First dataset	2017-09-12T04:00:04
Last dataset	2017-10-11T14:12:51
TSG1 valid data	635588

#### Calculation of 10min means

The calculation of 10min means included the removal of outliers outside a 2-times standard deviation for each data interval. The number of outliers for each parameter are given here.

Number of outliers >2*	umber of outliers >2*std		
Internal temperature	21201		
Conductivity	20567		
External temperature	22407		
Salinity	23045		
Result after outlier rem	oval		
Number 10-min-means	4237		

## **Manual flagging**

After processing the data were visually inspected. The whole data from a specific timestamp were deleted if there was only one parameter to be manually flagged. 89 data points were manually removed from the TSG1 dataset of PS109.

## Assigning navigation data

Data from the corrected mastertrack of cruise PS109 were assigned to the 10min means of TSG1. A speed filter of 0.5 knots minimum speed is applied to avoid redundant data. See Figure 1 and Figure 2 for the processed and corrected data of TSG1.

Number of speed flags: 1060

Number of data in final output file: 3088






Figure 1: 10min means of data from TSG1




Figure 2: Standard deviations of 10min means of data from TSG1



## Differences between internal and external temperature of TSG1 temperature sensors

Temperature differences between the internal and the external temperature sensors have to be small under normal circulation conditions. Means and standard deviations for the temperature differences as well as the number of data with a difference larger than 1 °C are given in the following table and are shown in Figure 3.

	TSG1 temperature difference		
	mean $\pm$ standard dev.	no. > 1°C	
Spot values	$0.0554 \pm 0.1309^{\circ}$ C	855	
10-min means	$0.0554 \pm 0.1282^{\circ}\text{C}$	6	




Figure 3: Differences between internal and external temperature sensors of TSG1

#### Result file

The result file is a plain text (tab-delimited values) file named **PS109\_surf\_oce.tab** with one data row in 10-min interval. For further information on the result file see the General Processing Report.



# 4 Appendix




Figure 4: Salinity data from TSG1






Figure 5: Temperature data from TSG1