

# CTD Data RV Heincke HE508

## Data Processing Report

### Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Workflow</b>	<b>1</b>
<b>3</b>	<b>Cruise details</b>	<b>3</b>
<b>4</b>	<b>Sensor Layout</b>	<b>3</b>
<b>5</b>	<b>Processing</b>	<b>3</b>
<b>6</b>	<b>Results</b>	<b>5</b>

Contact:

Andreas Wisotzki  
Alfred-Wegener-Institute  
Am Handelshafen 12, D-27570 Bremerhaven, GERMANY  
Mail: [info@awi.de](mailto:info@awi.de)

Processing Agency:

FIELAX  
Schleusenstr. 14, D-27568 Bremerhaven, GERMANY  
Mail: [info@fielax.de](mailto:info@fielax.de)

Ref.: CTD-HE508-report.pdf	Vers.: 1	Date: 2018/06/05	Status: final
----------------------------	----------	------------------	---------------


## 1 Introduction

This report describes the processing of CTD raw data acquired by Seabird SBE 911plus CTD on board RV Heincke during expedition HE508.

## 2 Workflow

The different steps of processing and validation are visualized in Figure 1. The CTD raw data are delivered from Andreas Wisotzki (AWI). The station book of the RV Heincke cruise is extracted from the DAVIS SHIP data base (<https://dship.awi.de>). The first CTD station and cast is processed manually in SBE Data Processing to configure the \*.psa Seabird routines *Data Conversion, Wild Edit, Bottle Summary, Split, Translate, Cell Thermal Mass, Loop Edit* and *Bin Average*. The Seabird routines are then run in a batch job *CTDjob* in ManageCTD to process the complete CTD data set. The downcast of each CTD station/cast is used for further processing. In *CTDjob* the start record and the lowest altimeter point of the downcast is selected. From the downcast data figures to compare both oxygen sensors are generated. The oxygen sensor choice and the offset between the two oxygen sensors is documented in the processing summary table. With the *Utilities* → *Dship Ebook* function of ManageCTD the DAVIS SHIP station book extraction is used for getting the header information of all CTD stations/casts of the cruise. ManageCTD *Utilities* → *Find Profile* function compares station times of the header with the entries in the station book to find out the correct naming of the stations and casts. In *CTDheader* in ManageCTD the header information of each CTD station/cast is displayed, controlled and corrected if necessary. *CTDdespike* in ManageCTD is used for a visual check of the data and to erase/interpolate spikes in the data if necessary. Additionally, a sensor pair (Temp1/Sal1 or Temp2/Sal2) is chosen for each station/cast of the RV Heincke cruise in *CTDdespike*.

ManageCTD *Utilities* → *CheckDoubleSensors* controls the quality of temperature and conductivity sensors. For this purpose outliers of too high sensor pair differences could be removed. The data is then converted to spreadsheet format with *dsp2odv* for visualization of the data in Ocean Data View (ODV). The second visual inspection of the CTD data allows a comparison with data from other CTD casts from close-by stations to verify the oxygen sensor data. Therefore, potential reference cruise data is downloaded from PANGAEA (<http://www.PANGAEA.de>). The reference data is converted to \*.mat format. In the ManageCTD Final Processing the CTD data is displayed together with the reference data. Bad data points, sensors or casts are interpolated or erased from the data set and filters are applied if necessary. The processed CTD data are written to text files and imported to PANGAEA (<http://www.PANGAEA.de>) for publication.



# CTD Processing Workflow

Heincke

Figure 1: CTD data Processing Workflow

### 3 Cruise details

Vessel name      RV Heincke  
 Cruise name      HE508  
 Cruise start     14.04.2018 Bremerhaven  
 Cruise end       22.04.2018 Helgoland  
 Cruise duration   9 days  
 No. of CTD casts  14

### 4 Sensor Layout

This chapter describes the CTD sensors mounted during this cruise:

SBE 911plus CTD (SN: 1015), SBE Instrument Configuration Version 7.23.0.1.

ID	Sensor Name	Serial No.	Calibration Date
55	TemperatureSensor	5354	11-Nov-17
3	ConductivitySensor	2470	08-Nov-17
45	PressureSensor	1015	26-Jan-17
55	TemperatureSensor	5375	11-Nov-17
3	ConductivitySensor	3573	08-Nov-17
0	AltimeterSensor	46466	23-Mar-09
71	WET_LabsCStar	1348DR	28-Jan-2016
20	FluoroWetlabECO_AFL_FL_Sensor	1365	15-Jan-2016
38	OxygenSensor	2292	02-Dec-17
38	OxygenSensor	3654	21-Dec-17

### 5 Processing

Details of processing procedures and processing parameters are described in *CTD Processing Logbook of RV Heincke* (hdl: [10013/epic.47427](https://nbn-resolving.org/urn:nbn:de:hbz:5:1-647427)).

#### Density Inversions and Manual Validation

Obvious outliers were removed manually. For the visual check density inversions  $> 0.005 \text{ kg/m}^3$  and  $> 0.01 \text{ kg/m}^3$  were flagged differently for display but not removed automatically. Decisions whether the flagged values were manually removed or not are based on the description in *CTD Processing Logbook of RV Heincke* (hdl: [10013/epic.47427](https://nbn-resolving.org/urn:nbn:de:hbz:5:1-647427)).

## Sensor Differences




Figure 2: Data accuracy of sensor pairs HE508

## 6 Results

A complete processing overview for each sensor at each station is summarized in the table in the Appendix (Figure 3).

### Double Sensor Check

In Figure 2, the absolute residuals between the sensorpairs are shown for the measured parameters *Temperature* and *Conductivity*, the derived parameter *Salinity* and the measured parameter *Oxygen*. Measurements in shallow water depths < 15 m (blue crosses) and gradients between two datapoints exceeding a defined threshold (red crosses) were omitted for accuracy calculation.

Parameter	Accuracy given by manufacturer	Measurements re- moved Surface 0-15m + gradi- ent filter	Remaining measure- ments within accuracy specifi- cations
Temperature	$\pm 0.001 \text{ } ^\circ\text{C}$	54.99%	71.55%
Conductivity	$\pm 0.003 \text{ mS/cm}$	50.85%	89.66%
Salinity	$\pm 0.0015 \text{ PSU}$	51.98%	79.61%
Oxygen	$\pm 2.0 \text{ \% of saturation}$	48.21%	0.73%

### Comments

- 14 CTD "max depth/on ground" entries in DShip station book
- 17 CTD raw data sets delivered
- 3 CTD casts were invalid or test (HE508\_2-1.hex, HE508\_23-1.hex, HE508\_37-1.hex,)
- 7 CTD casts had a wrong filename
- 14 CTD casts processed and uploaded
- of these 14 processed CTD casts:
  - 0 oxygen profiles deleted (spiky and not matching to reference casts)
  - 2 data points interpolated
  - 150 data points erased

## Result files

Text File (HE508\_phys\_oce.tab):

The format is a plain text (tab-delimited values) file.

Column separator	Tabulator "\t"
Column 1	Event label
Column 2	Date/Time of event
Column 3	Latitude of event
Column 4	Longitude of event
Column 5	Elevation of event
Column 6	DEPTH, water
Column 7	Pressure, water
Column 8	Temperature, water
Column 9	Conductivity
Column 10	Salinity
Column 11	Temperature, water, potential
Column 12	Density, sigma-theta (0)
Column 13	Oxygen
Column 14	Oxygen, saturation
Column 15	Attenuation, optical beam transmission
Column 16	Fluorometer
Column 17	Number of observations

Processing Report (CTD-HE508-report.pdf):

This PDF document.

Station HE508_ Abbr.	Gear	Date	Time	Position Latitude	Position Longitude	Depth (m)	File HE508_ ID	Sensor pair	Temp		Sal		Trans		Fluor		Oxy		2 Oxy Sensors		Oxygen reference		Comments			
									interp	erased	interp	erased	interp	erased	interp	erased	interp	erased	Sensor	Offset	cruse/sss-cc	dist. (km)		Offset		
1-1	CTD	14.04.2018	10:00:31	53° 50.145' N	008° 06.228' E	12.5	01-1.*	1	0	2	0	2	0	2	0	2	0	2	0	10	3654	0.30	HE461/1-1	7.20	~0.9	
1-3	CTD	14.04.2018	12:01:09	53° 50.677' N	008° 05.616' E	10.9	02-2.*	2	0	0	0	0	0	0	0	0	0	0	0	3654	0.31	HE461/1-1	8.39	~0.9	wrong station/cast no in file name	
2-1	CTD	15.04.2018	06:38:07	54° 08.626' N	007° 54.304' E	51.4	02a-1.*	1	0	0	0	0	0	0	0	0	0	0	0	3654	0.30	HE461/6-1	1.13	~0.5	wrong station no in file name	
4-1	CTD	15.04.2018	12:09:08	54° 05.427' N	007° 58.116' E	30.5	03-1.*	2	0	1	0	1	0	1	0	1	0	1	0	3654	0.19	HE461/3-1	0.33	~0.9	wrong station no in file name	
6-1	CTD	16.04.2018	06:35:26	54° 08.656' N	007° 52.866' E	52.3	06-1.*	1	0	0	0	0	0	0	0	0	0	0	0	3654	0.26	HE461/63-1	1.26	~1.0		
11-1	CTD	16.04.2018	12:52:12	54° 05.336' N	007° 58.016' E	30.7	11-1.*	2	1	0	1	0	0	0	0	0	0	0	2	0	3654	0.28	HE461/3-1	0.19	~0.9	
12-1	CTD	17.04.2018	06:37:33	54° 08.655' N	007° 52.791' E	52.3	12-1.*	2	0	0	0	0	0	0	0	0	0	0	0	3654	0.48	HE461/63-1	1.30	~0.9		
17-1	CTD	17.04.2018	13:10:29	54° 06.980' N	007° 34.654' E	35.8	13-1.*	2	0	0	0	0	0	0	0	0	0	0	0	3654	0.28	HE461/P8-4	3.82	~1.0	wrong station no in file name	
18-2	CTD	18.04.2018	12:35:49	54° 08.603' N	007° 52.888' E	55.8	18-1.*	1	0	0	0	0	0	0	0	0	0	0	0	3654	0.30	HE461/63-1	1.17	~1.1	no BTL-file; wrong cast no in file name	
19-1	CTD	19.04.2018	06:36:33	54° 08.825' N	007° 55.002' E	48.6	19-1.*	1	0	0	0	0	0	0	0	0	0	0	0	3654	0.31	HE461/6-1	0.41	~0.8		
22-1	CTD	19.04.2018	13:39:17	54° 10.113' N	007° 59.339' E	21.4	21-1.*	2	0	0	0	0	0	0	0	0	0	0	0	3654	0.29	HE461/16-1	1.84	~0.9	wrong station no in file name	
23-1	CTD	20.04.2018	06:44:28	54° 08.804' N	007° 55.029' E	49.1	23-2.*	1	0	27	0	27	0	27	0	27	0	27	0	3654	0.47	HE461/6-1	0.36	~0.6	upper ca 30m deleted; no BTL-file; wrong cast no in file name	
32-1	CTD	21.04.2018	05:57:13	54° 10.621' N	008° 01.360' E	28.2	32-1.*	1	0	0	0	0	0	0	0	0	0	0	0	3654	0.31	HE461/77-1	0.14	~1.0		
36-1	CTD	21.04.2018	11:59:13	54° 10.542' N	008° 01.448' E	27.4	36-1.*	1	0	0	0	0	0	0	0	0	0	0	0	3654	0.31	HE461/76-1	0.09	~1.2		
									1	30	1	30	0	30	0	30	0	30	2							

Figure 3: CTD data Processing Summary HE508  
Page 7 of 8






Figure 4: ODV Screenshot of HE508 CTD data  
Page 8 of 8