

RINEX: The Receiver Independent Exchange Format Version 2.10

Werner Gurtner
Astronomical Institute
University of Berne

Contents:

- 0. Revision History
 - 0.1 Revision Summary
 - 0.2 First Revision
 - 0.3 Later Revisions
 - 0.4 Version 2.10 Modifications
 - 0.5 Version 2.10 Revisions
- 1. THE PHILOSOPHY OF RINEX
- 2. GENERAL FORMAT DESCRIPTION
- 3. DEFINITION OF THE OBSERVABLES
- 4. THE EXCHANGE OF RINEX FILES:
- 5. RINEX VERSION 2 FEATURES
 - 5.1 Satellite Numbers:
 - 5.2 Order of the Header Records:
 - 5.3 Missing Items, Duration of the Validity of Values
 - 5.4 Event Flag Records
 - 5.5 Receiver Clock Offset
- 6. ADDITIONAL HINTS AND TIPS
 - 6.1 Version 1 / Version 2
 - 6.2 Leading Blanks in CHARACTER fields
 - 6.3 Variable-length Records
 - 6.4 Blank Fields
 - 6.5 2-Digit Years
 - 6.6 Fit Interval
 - 6.7 Satellite Health
 - 6.8 Transmission Time of Message (Navigation message file)
- 7. RINEX UNDER ANTISPOOFING (AS)
- 8. GLONASS Extensions
 - 8.1 RINEX Observation File
 - 8.1.1 Time System Identifier
 - 8.1.2 Pseudorange Definition
 - 8.1.3 More Than 12 Satellites per Epoch
 - 8.2 RINEX Navigation Files for GLONASS
- 9. RINEX Extensions for Geostationary Satellites (GPS Signal Payloads)
 - 9.1 RINEX Observation Files for GEO Satellites
 - 9.2 RINEX Navigation Message Files for GEO Satellites
- 10. REFERENCES
- 11. RINEX VERSION 2.10 FORMAT DEFINITIONS AND EXAMPLES
 - A 1 GPS OBSERVATION DATA FILE - HEADER SECTION DESCRIPTION
 - A 2 GPS OBSERVATION DATA FILE - DATA RECORD DESCRIPTION
 - A 3 GPS NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION
 - A 4 GPS NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION
 - A 5 METEOROLOGICAL DATA FILE - HEADER SECTION DESCRIPTION

A 5 METEOROLOGICAL DATA FILE - DATA RECORD DESCRIPTION
 A 7 GPS OBSERVATION DATA FILE - EXAMPLE
 A 8 GPS NAVIGATION MESSAGE FILE - EXAMPLE
 A 9 METEOROLOGICAL DATA FILE - EXAMPLE
 A10 GLONASS NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION
 A11 GLONASS NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION
 A12 GLONASS NAVIGATION MESSAGE FILE - EXAMPLE
 A13 GLONASS OBSERVATION FILE - EXAMPLE
 A14 MIXED GPS/GLONASS OBSERVATION FILE - EXAMPLE
 A15 GEOSTATIONARY NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION
 A16 GEOSTATIONARY NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION
 A17 MIXED GPS/GEO OBSERVATION FILE - EXAMPLE
 A18 GEO NAVIGATION MESSAGE FILE - EXAMPLE

0. REVISION HISTORY

0.1 Revision Summary

First Revision, April 1993
 Clarification December 1993
 Doppler Definition: January 1994
 PR Clarification: October 1994
 Wlfact Clarification: February 1995
 Event Time Frame Clarification: May 1996
 Minor errors in the examples A7/A8: May 1996
 Naming convention for compressed met files; January 1997
 Continuation line clarifications: April 1997
 GLONASS Extensions: April 1997
 Met sensor description and position records: April 1997
 Wavelength factor clarifications: April 1997
 Error in example A12: CORR TO SYSTEM TIME, April 1997
 Redefinition of sv clock params in GLONASS Nav Mess Files: March 1998
 Naming conventions for compressed RINEX obs files: March 1998
 GPS week: No roll-over, continuous number: March 1998
 Error in compressed DOS file naming convention: July 1998
 Table A13 contained blank satellite identifiers: Sept 1998
 Discrepancy between Tables A5 and A9 removed: Sept 1998
 Phase data format overflow: Clarification: Oct 1998
 Message frame time Table A11: Clarification: Oct 1998
 RINEX Version 2.10 Modifications: July 1999
 Typo in paragraph 0.4 (epoch flag >1): Nov 1999
 Clarification regarding trailing blanks: Dec 1999
 Clarification regarding units of ZD,ZT, URA(GEO)
 Clarification regarding time system identifier of GEO obs files
 Clarification regarding time system identifier in TIME OF LAST record: Feb 2000
 Addition of GEO examples: February 2000
 Clarification of epoch field for event flag records: May 2000
 Table A6: Typos in format definition of epoch: May 2000
 Clarification of the GLONASS satellite identifier: June 2001
 Clarification of the floating point exponent format: January 2002
 Glonass frequency numbers -7 ... +13: December 2007

0.2 First Revision

The first documentation of the RINEX Version 2 Format was published by W. Gurtner and G. Mader in the CSTG GPS Bulletin of September/October 1990. The main reason for a revision is the new treatment of antispoofing data by the RINEX format (see chapter 7). Chapter 4 gives a recommendation for data compression procedures, especially useful when large amounts of data are exchanged through computer networks. In Table A3 in the original paper the definition of the "PGM / RUN BY / DATE" navigation header record was missing, although the example showed it. The redefinition of AODE/AODC to IODE/IODC also asked for an update of the format description. For consistency reasons we also defined a Version 2 format for the Meteorological Data files (inclusion of a END OF HEADER record and an optional MARKER NUMBER record).

The slight modification (or rather the definition of a bit in the Loss of Lock Indicator unused so far) to flag AS data is so small a change that we decided

to NOT increase the version number!

0.3 Later Revisions

* URA Clarification (10-Dec-93):

The user range accuracy in the Navigation Message File did not contain a definition of the units: There existed two ways of interpretation: Either the 4 bit value from the original message or the converted value in meters according to GPS ICD-200. In order to simplify the interpretation for the user of the RINEX files I propose the bits to be converted into meters prior to RINEX file creation.

* GLONASS Extensions:

In March 1997 a proposal for extensions to the current RINEX definitions based on experiences collected with GLONASS only and mixed GPS/GLONASS data files was circulated among several instrument manufacturers and software developers.

The results of the call for comments have been worked into this document. A separate document (glonass.txt) summarizes just the necessary extensions.

- * A blank satellite identifier is allowed in pure GPS files only
- * Met sensor description and position records were added to facilitate the precise use of met values.
- * Description and examples for wavelength factors and their temporary changes (bit 1 of LLI) clarified.
- * The RINEX documentation distributed in spring 1997 contained definitions for the GLONASS satellite clock offset and drift with the intention to have them defined identically to the GPS values. Unfortunately the GLONASS Interface Document consulted had a sign error in one of the formulae.

The values should be stored into the RINEX file as $-\text{TauN}$, $+\text{GammaN}$, $-\text{TauC}$. The original definition asked for $-\text{TauN}$, $-\text{GammaN}$, $+\text{TauC}$. See paragraph 8.2.

To avoid problems with files created with the original definitions a real valued version number (2.01) has been introduced for GLONASS nav mess files.

- * IGS decided to use the Hatanaka compression scheme for RINEX observation files. Below the corresponding RINEX file name conventions are included as recommendations. The DOS naming (extension .yyE) was wrongly set to .yyY in the March 1998 version of the document.
- * GPS week: The GPS week number in all RINEX files is a continuous number not affected by the 1024 roll-over, it runs from 1023 over 1024 to 1025 etc.
- * A discrepancy between the definition of the header line fields of met sensor description and position in Table A5 and the example in Table A9 was removed. The latter was correct.
- * Clarification for phase data format overflows: Add or subtract a suitable number of cycles, set LLI flag.
- * Clarification for the GLONASS satellite identifier: "Almanac number" was somewhat ambiguous. It has been replaced by "slot number" within the satellite constellation.

0.4 Version 2.10 Modifications

The modifications leading to Version 2.10 include:

- Fractional version number
- Zero padding of 2-digit year values (years 2000-2009 --> 00-09)

- Field length of time of first obs (1/10 microsecond resolution)
- Non-integer sampling rate (INTERVAL header record)
- Header records now allowed after all epoch flags >1
- Additional obs types in obs files: S1, S2 (raw signal strength values)
- Receiver clock offset header line to clarify applied corrections
- Default wavelength factor header line mandatory
- Inmarsat GPS payloads: New satellite system definition, new nav mess files
- Curve fit interval in GPS nav mess file
- Redefinition of SV health value in GPS nav mess file
- Additional obs types in met files (ZD, ZT)

0.5 Version 2.10 Revisions

- * "Header records now allowed after all epoch flags >2" in paragraph 0.4 should read ">1"
- * The original intention of the RINEX format was to allow for variable record lengths of the ASCII files to minimize the file size. Empty fields or unknown values can either be represented by zeroes or blank space. Most RINEX converters removed trailing blank to further reduce the file size. The documentation was not clear enough to explicitly allow for this practice (paragraphs 2, 5.3, 9.1).
- * The time system identifier of GPS observations generated by GEO payloads defaults to GPS (explicitly stated now in paragraph 9.1)
- * The time system identifier in the TIME OF LAST OBS header record has to be identical to the one in the TIME OF FIRST OBS record
- * Clarification of Table A2 to be compatible with examples of Table A7:
For event flags without significant epoch the epoch fields can be left blank.
Table A6: Format for epoch contained obvious errors
- * Clarification of the floating point exponent format in navigation message files (two digits, E,e,D,d letters)
- * The newer GLONASS satellites started using frequency numbers in the 0 to -7 range. Table A11 BROADCAST ORBIT - 2 was modified accordingly.

1. THE PHILOSOPHY OF RINEX

The first proposal for the "Receiver Independent Exchange Format" RINEX has been developed by the Astronomical Institute of the University of Berne for the easy exchange of the GPS data to be collected during the large European GPS campaign EUREF 89, which involved more than 60 GPS receivers of 4 different manufacturers. The governing aspect during the development was the following fact:

Most geodetic processing software for GPS data use a well-defined set of observables:

- the carrier-phase measurement at one or both carriers (actually being a measurement on the beat frequency between the received carrier of the satellite signal and a receiver-generated reference frequency).
- the pseudorange (code) measurement, equivalent to the difference of the time of reception (expressed in the time frame of the receiver) and the time of transmission (expressed in the time frame of the satellite) of a distinct satellite signal.
- the observation time being the reading of the receiver clock at the instant of validity of the carrier-phase and/or the code measurements.

Usually the software assumes that the observation time is valid for both the phase AND the code measurements, AND for all satellites observed.

Consequently all these programs do not need most of the information that is usually stored by the receivers: They need phase, code, and time in the

above mentioned definitions, and some station-related information like station name, antenna height, etc.

2. GENERAL FORMAT DESCRIPTION

Currently the format consists of six ASCII file types:

1. Observation Data File
2. Navigation Message File
3. Meteorological Data File
4. GLONASS Navigation Message File
5. GEO Navigation Message File
6. Satellite and Receiver Clock Date File

(The format definition of the clock files has been published in 1998 in a separate document by Jim Ray and Werner Gurtner, available at the IGS Central Bureau Information System: ftp://igs.cb.jpl.nasa.gov/igs.cb/data/format/rinex_clock.txt).

Each file type consists of a header section and a data section. The header section contains global information for the entire file and is placed at the beginning of the file. The header section contains header labels in columns 61-80 for each line contained in the header section. These labels are mandatory and must appear exactly as given in these descriptions and examples.

The format has been optimized for minimum space requirements independent from the number of different observation types of a specific receiver by indicating in the header the types of observations to be stored. In computer systems allowing variable record lengths the observation records may be kept as short as possible. Trailing blanks can be removed from the records. The maximum record length is 80 bytes per record.

Each Observation file and each Meteorological Data file basically contain the data from one site and one session. RINEX Version 2 also allows to include observation data from more than one site subsequently occupied by a roving receiver in rapid static or kinematic applications. Although Version 2 allows to insert header records into the data field we do not recommend to concatenate data of more than one receiver (or antenna) into the same file, even if the data do not overlap in time.

If data from more than one receiver has to be exchanged it would not be economical to include the identical satellite messages collected by the different receivers several times. Therefore the Navigation Message File from one receiver may be exchanged or a composite Navigation Message File created containing non-redundant information from several receivers in order to make the most complete file.

The format of the data records of the RINEX Version 1 Navigation Message file is identical to the former NGS exchange format.

The actual format descriptions as well as examples are given in the Tables at the end of the paper.

3. DEFINITION OF THE OBSERVABLES

GPS observables include three fundamental quantities that need to be defined: Time, Phase, and Range.

TIME:

The time of the measurement is the receiver time of the received signals. It is identical for the phase and range measurements and is identical for all satellites observed at that epoch. It is expressed in GPS time (not Universal Time).

PSEUDO-RANGE:

The pseudo-range (PR) is the distance from the receiver antenna to the satellite antenna including receiver and satellite clock offsets (and other biases, such as atmospheric delays):

$$\text{PR} = \text{distance} + c * (\text{receiver clock offset} - \text{satellite clock offset} + \text{other biases})$$

so that the pseudo-range reflects the actual behavior of the receiver and satellite clocks. The pseudo-range is stored in units of meters.

See also clarifications for pseudoranges in mixed GPS/GLONASS files in chapter 8.1.

PHASE:

The phase is the carrier-phase measured in whole cycles at both L1 and L2. The half-cycles measured by squaring-type receivers must be converted to whole cycles and flagged by the wavelength factor in the header section.

The phase changes in the same sense as the range (negative doppler). The phase observations between epochs must be connected by including the integer number of cycles. The phase observations will not contain any systematic drifts from intentional offsets of the reference oscillators.

The observables are not corrected for external effects like atmospheric refraction, satellite clock offsets, etc.

If the receiver or the converter software adjusts the measurements using the real-time-derived receiver clock offsets $dT(r)$, the consistency of the 3 quantities phase / pseudo-range / epoch must be maintained, i.e. the receiver clock correction should be applied to all 3 observables:

$$\begin{aligned} \text{Time}(\text{corr}) &= \text{Time}(r) - dT(r) \\ \text{PR}(\text{corr}) &= \text{PR}(r) - dT(r) * c \\ \text{phase}(\text{corr}) &= \text{phase}(r) - dT(r) * \text{freq} \end{aligned}$$

DOPPLER:

The sign of the doppler shift as additional observable is defined as usual: Positive for approaching satellites.

4. THE EXCHANGE OF RINEX FILES:

We recommend using the following naming convention for RINEX files:

ssssdddf.yyt	ssss:	4-character station name designator
	ddd:	day of the year of first record
	f:	file sequence number within day
	0:	file contains all the existing data of the current day
	yy:	year
	t:	file type:
	O:	Observation file
	N:	Navigation file
	M:	Meteorological data file
	G:	GLONASS Navigation file
	H:	Geostationary GPS payload nav mess file
	B:	Geostationary GPS payload broadcast data
	C:	Clock files (see separate documentation)

When data transmission times or storage volumes are critical we recommend compressing the files prior to storage or transmission using the UNIX "compress" und "uncompress" programs. Compatible routines are available on VAX/VMS and PC/DOS systems, as well.

Proposed naming conventions for the compressed files:

File Types	UNIX	VMS	DOS
Obs Files	ssssdddf.yyO.Z	ssssdddf.yyO_Z	ssssdddf.yyY
Obs Files (Hatanaka compr)	ssssdddf.yyD.Z	ssssdddf.yyD_Z	ssssdddf.yyE
GPS Nav Files	ssssdddf.yyN.Z	ssssdddf.yyN_Z	ssssdddf.yyX
GLONASS Nav File	ssssdddf.yyG.Z	ssssdddf.yyG_Z	ssssdddf.yyV
GEO Nav Files	ssssdddf.yyH.Z	ssssdddf.yyH_Z	ssssdddf.yyU
GEO Broadcast Files	ssssdddf.yyB.Z	ssssdddf.yyB_Z	
Met Data Files	ssssdddf.yyM.Z	ssssdddf.yyM_Z	ssssdddf.yyW
Clock Files (see sep.doc.)	ssssdddf.yyC.Z	ssssdddf.yyC_Z	

References for the Hatanaka compression scheme: See e.g.

<ftp://igsch.jpl.nasa.gov/igsch/software/rnxcmp/docs/>

IGSMails 1525,1686,1726,1763,1785

5. RINEX VERSION 2 FEATURES

The following section contains features that have been introduced for RINEX Version 2:

5.1 Satellite Numbers:

Version 2 has been prepared to contain GLONASS or other satellite systems' observations. Therefore we have to be able to distinguish the satellites of the different systems: We precede the 2-digit satellite number with a system identifier.

```
snn          s:    satellite system identifier
                G or blank : GPS
                R           : GLONASS
                S           : Geostationary signal payload
                T           : Transit

                nn:    - PRN (GPS), slot number (GLONASS)
                    - PRN-100 (GEO)
                    - two-digit Transit satellite number
```

Note: G is mandatory in mixed GPS/GLONASS files

(blank default modified in April 1997)

5.2 Order of the Header Records:

As the record descriptors in columns 61-80 are mandatory, the programs reading a RINEX Version 2 header are able to decode the header records with formats according to the record descriptor, provided the records have been first read into an internal buffer.

We therefore propose to allow free ordering of the header records, with the following exceptions:

- The "RINEX VERSION / TYPE" record must be the first record in a file
- The default "WAVELENGTH FACT L1/2" record must precede all records defining wavelength factors for individual satellites
- The "# OF SATELLITES" record (if present) should be immediately followed by the corresponding number of "PRN / # OF OBS" records. (These records may be handy for documentary purposes. However, since they may only be created after having read the whole raw data file we define them to be optional.

5.3 Missing Items, Duration of the Validity of Values

Items that are not known at the file creation time can be set to zero or blank or the respective record may be completely omitted. Consequently items of missing header records will be set to zero or blank by the program reading RINEX files. Trailing blanks may be truncated from the record.

Each value remains valid until changed by an additional header record.

5.4 Event Flag Records

The "number of satellites" also corresponds to the number of records of the same epoch followed. Therefore it may be used to skip the appropriate number of records if certain event flags are not to be evaluated in detail.

5.5 Receiver Clock Offset

A large number of users asked to optionally include a receiver-derived clock offset into the RINEX format. In order to remove uncertainties if the data (epoch, pseudorange, phase) have been previously corrected or not by the reported clock offset, RINEX Version 2.10 requests a clarifying (new) header record.

It would then be possible to reconstruct the original observations if necessary.

As the output format for the receiver-derived clock offset is limited to nanoseconds the offset should be rounded to the nearest nanosecond before it is used to correct the observables in order to guarantee correct reconstruction.

6. ADDITIONAL HINTS AND TIPS

6.1 Version 1 / Version 2

Programs developed to read RINEX Version 1 files have to verify the version number. Version 2 files may look different (version number, END OF HEADER record, receiver and antenna serial number alphanumeric) even if they do not use any of the new features

6.2 Leading Blanks in CHARACTER fields

We propose that routines to read RINEX Version 2 files automatically delete leading blanks in any CHARACTER input field. Routines creating RINEX Version 2 files should also left-justify all variables in the CHARACTER fields.

6.3 Variable-length Records

DOS, and other, files may have variable record lengths, so we recommend to first read each observation record into a 80-character blank string and decode the data afterwards. In variable length records, empty data fields at the end of a record may be missing, especially in the case of the optional receiver clock offset.

6.4 Blank Fields

In view of future modifications we recommend to carefully skip any fields currently defined to be blank (Format fields nX), because they may be assigned to new contents in future versions.

6.5 2-Digit Years

RINEX version 2 stores the years of data records with two digits only. The header of observation files contains a TIME OF FIRST OBS record with the full four-digit year, the GPS nav messages contain the GPS week numbers. From these two data items the unambiguous year can easily be reconstructed.

A hundred-year ambiguity occurs in the met data and GLONASS and GEO nav messages: Instead of introducing a new TIME OF FIRST OBS header line it is safeto stipulate that any two-digit years in RINEX Version 1 and Version 2.xx files are understood to represent

80-99: 1980-1999
00-79: 2000-2079

Full 4-digit year fields could then be defined by a future RINEX version 3.

6.6 Fit Interval

Bit 17 in word 10 of subframe 2 is a "fit interval" flag which indicates the curve-fit interval used by the GPS Control Segment in determining the ephemeris parameters, as follows (see ICD-GPS-200, 20.3.3.4.3.1):

0 = 4 hours
1 = greater than 4 hours.

Together with the IODC values and Table 20-XII the actual fit interval can be determined. The second value in the last record of each message shall contain the fit interval in hours determined using IODC, fit flag, and Table 20-XII, according to the Interface Document ICD-GPS-200.

6.7 Satellite Health

The health of the signal components (bits 18 to 22 of word three in subframe one) are now (Version 2.10) included into the health value reported in the second field of the sixth nav mess records.

A program reading RINEX files could easily decide if bit 17 only or all bits (17-22) have been written:

RINEX Value: 0 Health OK
RINEX Value: 1 Health not OK (bits 18-22 not stored)
RINEX Value: >32 Health not OK (bits 18-22 stored)

6.8 Transmission Time of Message (Navigation message file)

The transmission time of message can be shortly before midnight Saturday/Sunday, the TOE and TOC of the message already in the next week. As the reported week in the RINEX nav message (BROADCAST ORBIT - 5 record) goes with ToE (this is different from the GPS week in the original satellite message!), the transmission time of message should be reduced by 604800 (i.e., will become negative) to also refer to the same week.

7. RINEX UNDER ANTISPOOFING (AS)

Some receivers generate code delay differences between the first and second frequency using cross-correlation techniques when AS is on and may recover the phase observations on L2 in full cycles. Using the C/A code delay on L1 and the observed difference it is possible to generate a code delay observation for the second frequency.

Other receivers recover P code observations by breaking down the Y code into P and W code.

Most of these observations may suffer from an increased noise level. In

to remove the contributions of the leap seconds from the pseudoranges.

"leap_seconds" is the actual number of leap seconds between GPS and GLONASS (UTC) time, as broadcast in the GPS almanac and distributed in Circular T of BIPM.

8.1.3 More Than 12 Satellites per Epoch

The format of the epoch / satellite line in the observation record part of the RINEX Observation files has only been defined for up to 12 satellites per epoch. We explicitly define now the format of the continuation lines, see Table A2.

8.2 RINEX Navigation Files for GLONASS

As the GLONASS navigation message differs in contents from the GPS message too much, a special GLONASS navigation message file format has been defined.

The header section and the first data record (epoch, satellite clock information) is similar to the GPS navigation file. The following records contain the satellite position, velocity and acceleration, the clock and frequency biases as well as auxiliary information as health, satellite frequency (channel), age of the information.

The corrections of the satellite time to UTC are as follows:

```
GPS      : Tutc = Tsv - af0 - af1 *(Tsv-Toc) - ... - A0 - ... - leap_sec
GLONASS: Tutc = Tsv + TauN - GammaN*(Tsv-Tb)          + TauC
```

*** In order to use the same sign conventions for the GLONASS corrections as in the GPS navigation files, the broadcast GLONASS values are stored as:

-TauN, +GammaN, -TauC.

The time tags in the GLONASS navigation files are given in UTC (i.e. not Moscow time or GPS time).

File naming convention: See above.

9. RINEX Extensions for Geostationary Satellites (GPS Signal Payloads)

With the implementation of GNSS programs, GPS-like ranging measurements can be performed on geostationary navigation payloads.

RINEX Version 2.10 defines the necessary extensions to handle such data in RINEX files for data exchange and postprocessing purposes.

9.1 RINEX Observation Files for GEO Satellites

A new satellite system identifier has been defined for the geostationary GPS signal payloads: "S", to be used in the RINEX VERSION / TYPE header line and in the satellite identifier 'snn', nn being the GEO PRN number minus 100.

e.g.: PRN = 120 --> 'snn' = "S20"

In mixed dual frequency GPS satellite / single frequency GEO payload observation files the fields for the second frequency observations of GEO satellites remain blank, are set to zero values or (if last in the record) can be truncated.

The time system identifier of GEO satellites generating GPS signals defaults to GPS time.

9.2 RINEX Navigation Message Files for GEO Satellites

As the GEO broadcast orbit format differs from the GPS message a special GEO navigation message file format has been defined which is nearly identical with the GLONASS nav mess file format.

The header section contains informations about the generating program, comments, and the difference between the GEO system time and UTC.

The first data record contains the epoch and satellite clock information, the following records contain the satellite position, velocity and acceleration and auxiliary information such as health, age of the data, etc.

The time tags in the GEO navigation files are given in the GPS time frame, i.e. not UTC.

The corrections of the satellite time to UTC are as follows:

$$\text{GEO} \quad : \text{Tutc} = \text{Tsv} - \text{aGf0} - \text{aGf1} * (\text{Tsv} - \text{Toe}) - \text{W0} - \text{leap_sec}$$

W0 being the correction to transform the GEO system time to UTC. Toe, aGf0, aGf1 see below in the format definition tables.

* References for the definition of the accuracy and health codes still have *
 * to be defined. *
 * Help is needed here by colleagues working with such GEO data! *

10. REFERENCES

Evans, A. (1989): "Summary of the Workshop on GPS Exchange Formats." Proceedings of the Fifth International Geodetic Symposium on Satellite Systems, pp. 917ff, Las Cruces.

Gurtner, W., G. Mader, D. Arthur (1989): "A Common Exchange Format for GPS Data." CSTG GPS Bulletin Vol.2 No.3, May/June 1989, National Geodetic Survey, Rockville.

Gurtner, W., G. Mader (1990): "The RINEX Format: Current Status, Future Developments." Proceedings of the Second International Symposium of Precise Positioning with the Global Positioning system, pp. 977ff, Ottawa.

Gurtner, W., G. Mader (1990): "Receiver Independent Exchange Format Version 2." CSTG GPS Bulletin Vol.3 No.3, Sept/Oct 1990, National Geodetic Survey, Rockville.

Gurtner, W. (1994): "RINEX: The Receiver-Independent Exchange Format." GPS World, Volume 5, Number 7, July 1994.

11. RINEX VERSION 2.10 FORMAT DEFINITIONS AND EXAMPLES

TABLE A1		
GPS OBSERVATION DATA FILE - HEADER SECTION DESCRIPTION		
HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT
RINEX VERSION / TYPE	- Format version (2.10)	F9.2,11X,
	- File type ('O' for Observation Data)	A1,19X,
	- Satellite System: blank or 'G': GPS	A1,19X
	'R': GLONASS	
	'S': Geostationary signal payload	
	'T': NNSS Transit	
	'M': Mixed	
PGM / RUN BY / DATE	- Name of program creating current file	A20,
	- Name of agency creating current file	A20,

	- Date of file creation	A20	
* COMMENT	Comment line(s)	A60	*
MARKER NAME	Name of antenna marker	A60	
* MARKER NUMBER	Number of antenna marker	A20	*
OBSERVER / AGENCY	Name of observer / agency	A20,A40	
REC # / TYPE / VERS	Receiver number, type, and version (Version: e.g. Internal Software Version)	3A20	
ANT # / TYPE	Antenna number and type	2A20	
APPROX POSITION XYZ	Approximate marker position (WGS84)	3F14.4	
ANTENNA: DELTA H/E/N	- Antenna height: Height of bottom surface of antenna above marker - Eccentricities of antenna center relative to marker to the east and north (all units in meters)	3F14.4	
WAVELENGTH FACT L1/2	- Default wavelength factors for L1 and L2 1: Full cycle ambiguities 2: Half cycle ambiguities (squaring) 0 (in L2): Single frequency instrument - zero or blank The default wavelength factor line is required and must precede satellite-specific lines.	2I6, I6	
* WAVELENGTH FACT L1/2	- Wavelength factors for L1 and L2 1: Full cycle ambiguities 2: Half cycle ambiguities (squaring) 0 (in L2): Single frequency instrument - Number of satellites to follow in list for which these factors are valid. - List of PRNs (satellite numbers with system identifier) These optional satellite specific lines may follow, if they identify a state different from the default values. Repeat record if necessary.	2I6, I6, 7(3X,A1,I2)	*
# / TYPES OF OBSERV	- Number of different observation types stored in the file - Observation types If more than 9 observation types: Use continuation line(s) The following observation types are defined in RINEX Version 2.10: L1, L2: Phase measurements on L1 and L2 C1 : Pseudorange using C/A-Code on L1 P1, P2: Pseudorange using P-Code on L1,L2 D1, D2: Doppler frequency on L1 and L2 T1, T2: Transit Integrated Doppler on 150 (T1) and 400 MHz (T2) S1, S2: Raw signal strengths or SNR values as given by the receiver for the L1,L2 phase observations	I6, 9(4X,A2) 6X,9(4X,A2)	

	Observations collected under Antispoofing are converted to "L2" or "P2" and flagged with bit 2 of loss of lock indicator (see Table A2).		
	Units : Phase : full cycles Pseudorange : meters Doppler : Hz Transit : cycles SNR etc : receiver-dependent		
	The sequence of the types in this record has to correspond to the sequence of the observations in the observation records		
* INTERVAL	Observation interval in seconds	F10.3	*
TIME OF FIRST OBS	- Time of first observation record (4-digit-year, month, day, hour, min, sec) - Time system: GPS (=GPS time system) GLO (=UTC time system) Compulsory in mixed GPS/GLONASS files Defaults: GPS for pure GPS files GLO for pure GLONASS files	5I6,F13.7, 5X,A3	
* TIME OF LAST OBS	- Time of last observation record (4-digit-year, month, day, hour, min, sec) - Time system: Same value as in TIME OF FIRST OBS record	5I6,F13.7, 5X,A3	*
* RCV CLOCK OFFS APPL	Epoch, code, and phase are corrected by applying the realtime-derived receiver clock offset: 1=yes, 0=no; default: 0=no Record required if clock offsets are reported in the EPOCH/SAT records	I6	*
* LEAP SECONDS	Number of leap seconds since 6-Jan-1980 Recommended for mixed GPS/GLONASS files	I6	*
* # OF SATELLITES	Number of satellites, for which observations are stored in the file	I6	*
* PRN / # OF OBS	PRN (sat.number), number of observations for each observation type indicated in the "# / TYPES OF OBSERV" - record. If more than 9 observation types: Use continuation line(s) This record is (these records are) repeated for each satellite present in the data file	3X,A1,I2,9I6 6X,9I6	*
END OF HEADER	Last record in the header section.	60X	

Records marked with * are optional

TABLE A2		
GPS OBSERVATION DATA FILE - DATA RECORD DESCRIPTION		
OBS. RECORD	DESCRIPTION	FORMAT
EPOCH/SAT or EVENT FLAG	- Epoch : - year (2 digits, padded with 0 if necessary) - month, day, hour, min,	1X,I2.2, 4(1X,I2),

	- sec		F11.7,
	- Epoch flag 0: OK		2X,I1,
	1: power failure between previous and current epoch		
	>1: Event flag		
	- Number of satellites in current epoch		I3,
	- List of PRNs (sat.numbers with system identifier, see 5.1) in current epoch		12(A1,I2),
	- receiver clock offset (seconds, optional)		F12.9
	If more than 12 satellites: Use continuation line(s)		32X, 12(A1,I2)
	If epoch flag 2-5:		
	- Event flag:		[2X,I1,]
	2: start moving antenna		
	3: new site occupation (end of kinem. data) (at least MARKER NAME record follows)		
	4: header information follows		
	5: external event (epoch is significant, same time frame as observation time tags)		
	- "Number of satellites" contains number of special records to follow. Maximum number of records: 999		[I3]
	- For events without significant epoch the epoch fields can be left blank		
	If epoch flag = 6:		
	6: cycle slip records follow to optionally report detected and repaired cycle slips (same format as OBSERVATIONS records; slip instead of observation; LLI and signal strength blank or zero)		
OBSERVATIONS	- Observation	rep. within record for	m(F14.3,
	- LLI	each obs.type (same seq	I1,
	- Signal strength	as given in header)	I1)
	If more than 5 observation types (=80 char): continue observations in next record.		
	This record is (these records are) repeated for each satellite given in EPOCH/SAT - record.		
	Observations:		
	Phase : Units in whole cycles of carrier		
	Code : Units in meters		
	Missing observations are written as 0.0 or blanks.		
	Phase values overflowing the fixed format F14.3 have to be clipped into the valid interval (e.g. add or subtract 10**9), set LLI indicator.		
	Loss of lock indicator (LLI). Range: 0-7		
	0 or blank: OK or not known		
	Bit 0 set : Lost lock between previous and current observation: cycle slip possible		
	Bit 1 set : Opposite wavelength factor to the one defined for the satellite by a previous WAVELENGTH FACT L1/2 line. Valid for the current epoch only.		
	Bit 2 set : Observation under Antispoofing (may suffer from increased noise)		

Bits 0 and 1 for phase only.
Signal strength projected into interval 1-9:
1: minimum possible signal strength
5: threshold for good S/N ratio
9: maximum possible signal strength
0 or blank: not known, don't care

TABLE A3		
GPS NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION		
HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT
RINEX VERSION / TYPE	- Format version (2.10) - File type ('N' for Navigation data)	F9.2,11X, A1,19X
PGM / RUN BY / DATE	- Name of program creating current file - Name of agency creating current file - Date of file creation	A20, A20, A20
*COMMENT	Comment line(s)	A60
*ION ALPHA	Ionosphere parameters A0-A3 of almanac (page 18 of subframe 4)	2X,4D12.4
*ION BETA	Ionosphere parameters B0-B3 of almanac	2X,4D12.4
*DELTA-UTC: A0,A1,T,W	Almanac parameters to compute time in UTC (page 18 of subframe 4) A0,A1: terms of polynomial T : reference time for UTC data W : UTC reference week number. Continuous number, not mod(1024)!	3X,2D19.12, 2I9)
*LEAP SECONDS	Delta time due to leap seconds	I6
END OF HEADER	Last record in the header section.	60X

Records marked with * are optional

TABLE A4		
GPS NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION		
OBS. RECORD	DESCRIPTION	FORMAT
PRN / EPOCH / SV CLK	- Satellite PRN number - Epoch: Toc - Time of Clock year (2 digits, padded with 0 if necessary) month day hour minute second - SV clock bias (seconds) - SV clock drift (sec/sec) - SV clock drift rate (sec/sec2)	I2, 1X,I2.2, 1X,I2, 1X,I2, 1X,I2, 1X,I2, F5.1, 3D19.12 *)
BROADCAST ORBIT - 1	- IODE Issue of Data, Ephemeris - Crs (meters) - Delta n (radians/sec)	3X,4D19.12

	- M0	(radians)	
BROADCAST ORBIT - 2	- Cuc	(radians)	3X,4D19.12
	- e Eccentricity		
	- Cus	(radians)	
	- sqrt(A)	(sqrt(m))	
BROADCAST ORBIT - 3	- Toe Time of Ephemeris		3X,4D19.12
		(sec of GPS week)	
	- Cic	(radians)	
	- OMEGA	(radians)	
	- CIS	(radians)	
BROADCAST ORBIT - 4	- i0	(radians)	3X,4D19.12
	- Crc	(meters)	
	- omega	(radians)	
	- OMEGA DOT	(radians/sec)	
BROADCAST ORBIT - 5	- IDOT	(radians/sec)	3X,4D19.12
	- Codes on L2 channel		
	- GPS Week # (to go with TOE)		
	Continuous number, not mod(1024)!		
	- L2 P data flag		
BROADCAST ORBIT - 6	- SV accuracy	(meters)	3X,4D19.12
	- SV health	(bits 17-22 w 3 sf 1)	
	- TGD	(seconds)	
	- IODC Issue of Data, Clock		
BROADCAST ORBIT - 7	- Transmission time of message	**)	3X,4D19.12
	(sec of GPS week, derived e.g.		
	from Z-count in Hand Over Word (HOW)		
	- Fit interval	(hours)	
	(see ICD-GPS-200, 20.3.4.4)		
	Zero if not known		
	- spare		
	- spare		

**) Adjust the Transmission time of message by -604800 to refer to the reported week, if necessary.

*) In order to account for the various compilers, E,e,D, and d are allowed letters between the fraction and exponent of all floating point numbers in the navigation message files. Zero-padded two-digit exponents are required, however.

TABLE A5			
METEOROLOGICAL DATA FILE - HEADER SECTION DESCRIPTION			
HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT	
RINEX VERSION / TYPE	- Format version (2.10)	F9.2,11X,	
	- File type ('M' for Meteorological Data)	A1,39X	
PGM / RUN BY / DATE	- Name of program creating current file	A20,	
	- Name of agency creating current file	A20,	
	- Date of file creation	A20	
* COMMENT	Comment line(s)	A60	*
MARKER NAME	Station Name (preferably identical to MARKER NAME in the associated Observation File)	A60	
* MARKER NUMBER	Station Number	A20	*

	(preferably identical to MARKER NUMBER in the associated Observation File)	
# / TYPES OF OBSERV	- Number of different observation types stored in the file - Observation types The following meteorological observation types are defined in RINEX Version 2: PR : Pressure (mbar) TD : Dry temperature (deg Celsius) HR : Relative Humidity (percent) ZW : Wet zenith path delay (millimeters) (for WVR data) ZD : Dry component of zenith path delay (millimeters) ZT : Total zenith path delay (millimeters) The sequence of the types in this record must correspond to the sequence of the measurements in the data records If more than 9 observation types are being used, use continuation lines with format (6X,9(4X,A2))	I6, 9(4X,A2)
SENSOR MOD/TYPER/ACC	Description of the met sensor - Model (manufacturer) - Type - Accuracy (same units as obs values) - Observation type Record is repeated for each observation type found in # / TYPES OF OBSERV record	A20, A20,6X, F7.1,4X, A2,1X
SENSOR POS XYZ/H	Approximate position of the met sensor - Geocentric coordinates X,Y,Z (ITRF or WGS-84) - Ellipsoidal height H - Observation type Set X,Y,Z to zero if not known. Make sure H refers to ITRF or WGS-84! Record required for barometer, recommended for other sensors.	3F14.4, 1F14.4, 1X,A2,1X
END OF HEADER	Last record in the header section.	60X

Records marked with * are optional

TABLE A6 METEOROLOGICAL DATA FILE - DATA RECORD DESCRIPTION		
OBS. RECORD	DESCRIPTION	FORMAT
EPOCH / MET	- Epoch in GPS time (not local time!) year (2 digits, padded with 0 if necessary) month,day,hour,min,sec The 2-digit years in RINEX Version 1 and 2.xx files are understood to represent 80-99: 1980-1999 and 00-79: 2000-2079	1X,I2.2, 5(1X,I2),
	- Met data in the same sequence as given in the header	mF7.1

```

|           | More than 8 met data types: Use continuation |4X,10F7.1,3X|
|           | lines                                           |           |
+-----+-----+-----+-----+-----+-----+-----+-----+

```

```

+-----+-----+-----+-----+-----+-----+-----+-----+
|                                     TABLE A7                                     |
|                                     GPS OBSERVATION DATA FILE - EXAMPLE         |
+-----+-----+-----+-----+-----+-----+-----+-----+

```

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

```

2.10          OBSERVATION DATA      M (MIXED)          RINEX VERSION / TYPE
BLANK OR G = GPS, R = GLONASS, T = TRANSIT, M = MIXED  COMMENT
XXRINEXO V9.9  AIUB                    24-MAR-01 14:43  PGM / RUN BY / DATE
EXAMPLE OF A MIXED RINEX FILE  COMMENT

```

```

A 9080
9080.1.34
BILL SMITH          ABC INSTITUTE
X1234A123          XX                      ZZZ
234                YY
  4375274.         587466.         4589095.
    .9030          .0000          .0000
  1  1
  1  2  6  G14  G15  G16  G17  G18  G19
  0
  4  P1  L1  L2  P2
18.000
2001  3  24  13  10  36.0000000

```

```

01  3  24  13  10  36.0000000  0  3G12G 9G 6
23629347.915          .300 8          -.353  23629364.158
20891534.648          -.120 9          -.358  20891541.292
20607600.189          -.430 9          .394  20607605.848
01  3  24  13  10  50.0000000  4  4
  1  2  2  G 9  G12

```

```

*** WAVELENGTH FACTOR CHANGED FOR 2 SATELLITES ***
    NOW 8 SATELLITES HAVE WL FACT 1 AND 2!

```

```

01  3  24  13  10  54.0000000  0  5G12G 9G 6R21R22
23619095.450          -53875.632 8          -41981.375  23619112.008
20886075.667          -28688.027 9          -22354.535  20886082.101
20611072.689          18247.789 9          14219.770  20611078.410
21345678.576          12345.567 5
22123456.789          23456.789 5
01  3  24  13  11  0.0000000  2  1

```

```

*** FROM NOW ON KINEMATIC DATA! ***

```

```

01  3  24  13  11  48.0000000  0  4G16G12G 9G 6
21110991.756          16119.980 7          12560.510  21110998.441
23588424.398          -215050.557 6          -167571.734  23588439.570
20869878.790          -113803.187 8          -88677.926  20869884.938
20621643.727          73797.462 7          57505.177  20621649.276
    3  4

```

```

A 9080
9080.1.34
.9030          .0000          .0000
--> THIS IS THE START OF A NEW SITE <--

```

```

01  3  24  13  12  6.0000000  0  4G16G12G 6G 9
21112589.384          24515.877 6          19102.763 3  21112596.187
23578228.338          -268624.234 7          -209317.284 4  23578244.398
20625218.088          92581.207 7          72141.846 4  20625223.795
20864539.693          -141858.836 8          -110539.435 5  20864545.943
01  3  24  13  13  1.2345678  5  0
    4  1

```

```

(AN EVENT FLAG WITH SIGNIFICANT EPOCH)

```

```

01  3  24  13  14  12.0000000  0  4G16G12G 9G 6
21124965.133          89551.30216          69779.62654  21124972.2754
23507272.372          -212616.150 7          -165674.789 5  23507288.421
20828010.354          -333820.093 6          -260119.395 5  20828017.129

```

20650944.902 227775.130 7 177487.651 4 20650950.363

4 1

*** ANTISPOOFING ON G 16 AND LOST LOCK COMMENT

01 3 24 13 14 12.0000000 6 2G16G 9
123456789.0 -9876543.5
0.0 -0.5

4 2

---> CYCLE SLIPS THAT HAVE BEEN APPLIED TO COMMENT
THE OBSERVATIONS COMMENT

01 3 24 13 14 48.0000000 0 4G16G12G 9G 6 -.123456234
21128884.159 110143.144 7 85825.18545 21128890.7764
23487131.045 -318463.297 7 -248152.72824 23487146.149
20817844.743 -387242.571 6 -301747.22925 20817851.322
20658519.895 267583.67817 208507.26234 20658525.869

4 4

*** SATELLITE G 9 THIS EPOCH ON WLFACT 1 (L2) COMMENT
*** G 6 LOST LOCK AND THIS EPOCH ON WLFACT 2 (L2) COMMENT
(OPPOSITE TO PREVIOUS SETTINGS) COMMENT

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

-----+-----+
| TABLE A8 |
| GPS NAVIGATION MESSAGE FILE - EXAMPLE |
-----+-----+

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

2.10 N: GPS NAV DATA RINEX VERSION / TYPE
XXRINEXN V2.10 AIUB 3-SEP-99 15:22 PGM / RUN BY / DATE
EXAMPLE OF VERSION 2.10 FORMAT COMMENT
.1676D-07 .2235D-07 -.1192D-06 -.1192D-06 ION ALPHA
.1208D+06 .1310D+06 -.1310D+06 -.1966D+06 ION BETA
.133179128170D-06 .107469588780D-12 552960 1025 DELTA-UTC: A0,A1,T,W
13 LEAP SECONDS
END OF HEADER

6 99 9 2 17 51 44.0 -.839701388031D-03 -.165982783074D-10 .000000000000D+00
.910000000000D+02 .934062500000D+02 .116040547840D-08 .162092304801D+00
.484101474285D-05 .626740418375D-02 .652112066746D-05 .515365489006D+04
.409904000000D+06 -.242143869400D-07 .329237003460D+00 -.596046447754D-07
.111541663136D+01 .326593750000D+03 .206958726335D+01 -.638312302555D-08
.307155651409D-09 .000000000000D+00 .102500000000D+04 .000000000000D+00
.000000000000D+00 .000000000000D+00 .000000000000D+00 .910000000000D+02
.406800000000D+06 .000000000000D+00
13 99 9 2 19 0 0.0 .490025617182D-03 .204636307899D-11 .000000000000D+00
.133000000000D+03 -.963125000000D+02 .146970407622D-08 .292961152146D+01
-.498816370964D-05 .200239347760D-02 .928156077862D-05 .515328476143D+04
.414000000000D+06 -.279396772385D-07 .243031939942D+01 -.558793544769D-07
.110192796930D+01 .271187500000D+03 -.232757915425D+01 -.619632953057D-08
-.785747015231D-11 .000000000000D+00 .102500000000D+04 .000000000000D+00
.000000000000D+00 .000000000000D+00 .000000000000D+00 .389000000000D+03
.410400000000D+06 .000000000000D+00

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

-----+-----+
| TABLE A9 |
| METEOROLOGICAL DATA FILE - EXAMPLE |
-----+-----+

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

2.10 METEOROLOGICAL DATA RINEX VERSION / TYPE
XXRINEXM V9.9 AIUB 3-APR-96 00:10 PGM / RUN BY / DATE
EXAMPLE OF A MET DATA FILE COMMENT
A 9080 MARKER NAME
3 PR TD HR # / TYPES OF OBSERV

```

PAROSCIENTIFIC      740-16B                0.2    PR SENSOR MOD/TYPE/ACC
HAENNI              0.1    TD SENSOR MOD/TYPE/ACC
ROTRONIC            I-240W                5.0    HR SENSOR MOD/TYPE/ACC
                   0.0          0.0          0.0    1234.5678 PR SENSOR POS XYZ/H
                                           END OF HEADER
96  4  1  0  0 15  987.1  10.6  89.5
96  4  1  0  0 30  987.2  10.9  90.0
96  4  1  0  0 45  987.1  11.6  89.0

```

```

-----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

TABLE A10			
GLONASS NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION			
HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT	
RINEX VERSION / TYPE	- Format version (2.10)	F9.2,11X,	#
	- File type ('G' = GLONASS nav mess data)	A1,39X	
PGM / RUN BY / DATE	- Name of program creating current file	A20,	
	- Name of agency creating current file	A20,	
	- Date of file creation (dd-mmm-yy hh:mm)	A20	
* COMMENT	Comment line(s)	A60	*
* CORR TO SYSTEM TIME	- Time of reference for system time corr (year, month, day)	3I6,	*
	- Correction to system time scale (sec) to correct GLONASS system time to UTC (SU)	3X,D19.12	
	(-TauC)	*)	
* LEAP SECONDS	Number of leap seconds since 6-Jan-1980	I6	*
END OF HEADER	Last record in the header section.	60X	

Records marked with * are optional

TABLE A11			
GLONASS NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION			
OBS. RECORD	DESCRIPTION	FORMAT	
PRN / EPOCH / SV CLK	- Satellite number:	I2,	
	Slot number in sat. constellation		
	- Epoch of ephemerides (UTC)		
	- year (2 digits, padded with 0, if necessary)	1X,I2.2,	
	- month,day,hour,minute,	4(1X,I2),	
	- second	F5.1,	
	- SV clock bias (sec) (-TauN)	D19.12,	
	- SV relative frequency bias (+GammaN)	D19.12,	
	- message frame time (tk)	D19.12	
	(0 .le. tk .lt. 86400 sec of day UTC)		
		*)	
	The 2-digit years in RINEX 1 and 2.xx files are understood to represent 80-99: 1980-1999 and 00-79: 2000-2079		
BROADCAST ORBIT - 1	- Satellite position X (km)	3X,4D19.12	
	- velocity X dot (km/sec)		
	- X acceleration (km/sec2)		
	- health (0=OK) (Bn)		

BROADCAST ORBIT - 2	-	Satellite position Y	(km)	3X,4D19.12
	-	velocity Y dot	(km/sec)	
	-	Y acceleration	(km/sec2)	
	-	frequency number	(-7 ... +13)	
BROADCAST ORBIT - 3	-	Satellite position Z	(km)	3X,4D19.12
	-	velocity Z dot	(km/sec)	
	-	Z acceleration	(km/sec2)	
	-	Age of oper. information	(days) (E)	

*) In order to account for the various compilers, E,e,D, and d are allowed letters between the fraction and exponent of all floating point numbers in the navigation message files. Zero-padded two-digit exponents are required, however.

TABLE A12
GLONASS NAVIGATION MESSAGE FILE - EXAMPLE

-----1|0-----2|0-----3|0-----4|0-----5|0-----6|0-----7|0-----8|

2.10	GLONASS NAV DATA	RINEX VERSION / TYPE
ASRINEXG V1.1.0 VM	AIUB	19-FEB-98 10:42
STATION ZIMMERWALD		PGM / RUN BY / DATE
1998 2 16	0.379979610443D-06	COMMENT
		CORR TO SYSTEM TIME
		END OF HEADER
3 98 2 15 0 15	0.0 0.163525342941D-03 0.363797880709D-11	0.108000000000D+05
	0.106275903320D+05-0.348924636841D+00 0.931322574615D-09	0.000000000000D+00
	-0.944422070313D+04 0.288163375854D+01 0.931322574615D-09	0.210000000000D+02
	0.212257280273D+05 0.144599342346D+01-0.186264514923D-08	0.300000000000D+01
4 98 2 15 0 15	0.0 0.179599039257D-03 0.636646291241D-11	0.122400000000D+05
	0.562136621094D+04-0.289074897766D+00-0.931322574615D-09	0.000000000000D+00
	-0.236819248047D+05 0.102263259888D+01 0.931322574615D-09	0.120000000000D+02
	0.762532910156D+04 0.339257907867D+01 0.000000000000D+00	0.300000000000D+01
11 98 2 15 0 15	0.0-0.559808686376D-04-0.272848410532D-11	0.108600000000D+05
	-0.350348437500D+04-0.255325126648D+01 0.931322574615D-09	0.000000000000D+00
	0.106803754883D+05-0.182923507690D+01 0.000000000000D+00	0.400000000000D+01
	0.228762856445D+05 0.447064399719D+00-0.186264514923D-08	0.300000000000D+01
12 98 2 15 0 15	0.0 0.199414789677D-04-0.181898940355D-11	0.108900000000D+05
	0.131731816406D+05-0.143945598602D+01 0.372529029846D-08	0.000000000000D+00
	0.171148715820D+05-0.118937969208D+01 0.931322574615D-09	0.220000000000D+02
	0.135737919922D+05 0.288976097107D+01-0.931322574615D-09	0.300000000000D+01

-----1|0-----2|0-----3|0-----4|0-----5|0-----6|0-----7|0-----8|

TABLE A13
GLONASS OBSERVATION FILE - EXAMPLE

-----1|0-----2|0-----3|0-----4|0-----5|0-----6|0-----7|0-----8|

2.10	OBSERVATION DATA	R (GLONASS)	RINEX VERSION / TYPE
XXRINEXO V1.1	AIUB	27-AUG-93 07:23	PGM / RUN BY / DATE
TST1			MARKER NAME
VIEWEG	BRAUNSCHWEIG		OBSERVER / AGENCY
100	XX-RECEIVER	1.0	REC # / TYPE / VERS
101	XX-ANTENNA		ANT # / TYPE
3844808.114	715426.767	5021804.854	APPROX POSITION XYZ
1.2340	.0000	.0000	ANTENNA: DELTA H/E/N
1 1			WAVELENGTH FACT L1/2
2 C1 L1			# / TYPES OF OBSERV
10.000			INTERVAL

```

1993      8      23      14      24      40.0490000      GLO      TIME OF FIRST OBS
                                                END OF HEADER
93  8 23 14 24 40.0490000  0  3  2R01R21
23986839.824      20520.565  5
23707804.625      19937.231  5
23834065.096      -9334.581  5
93  8 23 14 24 50.0490000  0  3  2R01R21
23992341.033      49856.525  5
23713141.002      48479.290  5
23831189.435      -24821.796  5
93  8 23 14 25 .0490000  0  3  2R01R21
23997824.854      79217.202  5
23718494.110      77092.992  5
23828329.946      -40219.918  5
93  8 23 14 25 10.0490000  0  5  2R05R17R01R21
24003328.910      108602.422  5
24933965.449      -19202.780  5
22203326.578      -2987.327  5
23723851.686      105777.849  5
23825485.526      -55529.205  5
93  8 23 14 25 20.0490010  0  5  2R05R17R01R21
24008828.023      138012.178  5
24927995.616      -51188.500  5
22202547.907      -7213.298  5
23729236.758      134533.636  5
23822662.277      -70749.590  5
93  8 23 14 25 30.0490000  0  5  2R05R17R01R21
24014330.779      167446.477  5
24922041.288      -83151.666  5
22201767.457      -11388.909  5
23734633.024      163360.131  5
23819848.894      -85881.102  5

```

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

```

+-----+
|                                     TABLE A14                                     |
|                                     MIXED GPS/GLONASS OBSERVATION FILE - EXAMPLE   |
+-----+

```

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

```

2.10      OBSERVATION DATA      M (MIXED)      RINEX VERSION / TYPE
YYRINEXO V2.8.1 VM      AIUB      6-FEB-00 13:59      PGM / RUN BY / DATE
TST2      MARKER NAME
001-02-A      MARKER NUMBER
JIM      Y-COMPANY      OBSERVER / AGENCY
1      YY-RECEIVER      2.0.1      REC # / TYPE / VERS
1      GEODETIC L1      ANT # / TYPE
3851178.1849      -80151.4072      5066671.1013      APPROX POSITION XYZ
1.2340      0.0000      0.0000      ANTENNA: DELTA H/E/N
1      0      WAVELENGTH FACT L1/2
2      C1      L1      # / TYPES OF OBSERV
10.000      INTERVAL
11      LEAP SECONDS
2000      2      6      11      53      0.0000000      GPS      TIME OF FIRST OBS
                                                END OF HEADER
00  2  6 11 53  0.0000000  0 14G23G07G02G05G26G09G21R20R19R12R02R11
R10R03
22576523.586      -11256947.60212
22360162.704      -16225110.75413
24484865.974      14662682.882  2
21950524.331      -13784707.24912
22507304.252      9846064.848  2
20148742.213      -20988953.712  4
22800149.591      -16650822.70012
19811403.273      -25116169.741  3
23046997.513      -3264701.688  2

```

```

22778170.622 -821857836.745 1
22221283.991 -988088156.884 2
19300913.475 -83282658.19013
20309075.579 -672668843.84713
23397403.484 -285457101.34211
00 2 6 11 53 10.0000000 0 14G23G07G02G05G26G09G21R20R19R12R02R11
R10R03
22578985.016 -11244012.910 2
22359738.890 -16227337.841 2
24490324.818 14691368.710 2
21944376.706 -13817012.849 2
22512598.731 9873887.580 2
20147322.111 -20996416.338 4
22798942.949 -16657163.594 2
19812513.509 -25110234.795 3
23053885.702 -3227854.397 2
22770607.029 -821898566.774 1
22222967.297 -988079145.989 2
19297913.736 -83298710.38413
20313087.618 -672647337.04113
23392352.454 -285484291.40311

```

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

TABLE A15		
GEOSTATIONARY NAVIGATION MESSAGE FILE - HEADER SECTION DESCRIPTION		
HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT
RINEX VERSION / TYPE	- Format version (2.10)	F9.2,11X,
	- File type ('H' = GEO nav mess data)	A1,39X
PGM / RUN BY / DATE	- Name of program creating current file	A20,
	- Name of agency creating current file	A20,
	- Date of file creation (dd-mmm-yy hh:mm)	A20
* COMMENT	Comment line(s)	A60
* CORR TO SYSTEM TIME	- Time of reference for system time corr	
	(year, month, day)	3I6,
	- Correction to transform the GEO system	3X,D19.12
	time to UTC (W0)	*)
* LEAP SECONDS	Number of leap seconds since 6-Jan-1980	I6
END OF HEADER	Last record in the header section.	60X

Records marked with * are optional

TABLE A16		
GEOSTATIONARY NAVIGATION MESSAGE FILE - DATA RECORD DESCRIPTION		
OBS. RECORD	DESCRIPTION	FORMAT
PRN / EPOCH / SV CLK	- Satellite number (PRN - 100)	I2,
	- Epoch of ephemerides (GPS) (Toe)	
	- year (2 digits, padded with 0	
	if necessary)	1X,I2.2,
	- month,day,hour,minute,	4(1X,I2),
	- second	F5.1,
	- SV clock bias (sec) (aGf0)	D19.12,
	- SV relative frequency bias (aGf1)	D19.12,
	- message frame time (sec of day GPS)	D19.12

BROADCAST ORBIT - 1	-	Satellite position X	(km)	3X,4D19.12
	-	velocity X dot	(km/sec)	
	-	X acceleration	(km/sec2)	*
	-	health (0=OK)		
BROADCAST ORBIT - 2	-	Satellite position Y	(km)	3X,4D19.12
	-	velocity Y dot	(km/sec)	
	-	Y acceleration	(km/sec2)	
	-	Accuracy code	(URA, meters)	
BROADCAST ORBIT - 3	-	Satellite position Z	(km)	3X,4D19.12
	-	velocity Z dot	(km/sec)	
	-	Z acceleration	(km/sec2)	
	-	spare		

*) In order to account for the various compilers, E,e,D, and d are allowed letters between the fraction and exponent of all floating point numbers in the navigation message files. Zero-padded two-digit exponents are required, however.

TABLE A17
MIXED GPS/GEO OBSERVATION FILE - EXAMPLE

```

-----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|
2.10      OBSERVATION DATA      M (MIXED)      RINEX VERSION / TYPE
RinExp V.2.0.2  TESTUSER          00-02-04 09:30  PGM / RUN BY / DATE
                                           COMMENT
The file contains L1 pseudorange and phase data of the  COMMENT
geostationary AOR-E satellite (PRN 120 = S20)          COMMENT
                                           COMMENT
TLSE D                                             MARKER NAME
ESTB                                             OBSERVER / AGENCY
SGL98030069  TESTAGENCY
                                           REC # / TYPE / VERS
                                           ANT # / TYPE
4629365.0750  112100.1790  4371619.4160  APPROX POSITION XYZ
0.0000      0.0000      0.0000      ANTENNA: DELTA H/E/N
1 1                                             WAVELENGTH FACT L1/2
4 C1 L1 L2 P2 # / TYPES OF OBSERV
1                                             INTERVAL
2000 1 13 14 45 0.000000 GPS TIME OF FIRST OBS
2000 1 13 15 0 0.000000 GPS TIME OF LAST OBS
0                                             RCV CLOCK OFFS APPL
                                           END OF HEADER
00 01 13 14 45 0.0000000 0 8G25G17G06G05G24G29G30S20 0.000535140
21839900.207 -236148.877 9 -184047.71049 21839901.4384
25151926.413 -161002.900 9 -125509.72447 25151935.8274
20531103.515 763336.059 9 594797.53149 20531105.0114
23001624.801 -432989.642 9 -337436.50348 23001628.1684
23610349.510 -384890.728 9 -299952.38848 23610354.3504
23954474.398 -151982.173 9 -118480.96847 23954481.1994
20622367.016 -332628.466 9 -259214.55249 20622367.8754
38137559.506 335849.135 9
00 01 13 14 45 1.0000000 0 8G25G17G06G05G24G29G30S20 0.000535144
21839500.278 -238250.743 9 -185685.52549 21839501.4814
25151246.148 -164576.503 9 -128294.33947 25151256.2614
20531084.382 763235.849 9 594719.44849 20531085.8784
23002123.430 -430369.237 9 -335394.62748 23002126.7114
23610670.127 -383205.864 9 -298639.51048 23610674.9834
23955051.773 -148948.417 9 -116117.00748 23955058.5034
20622558.579 -331621.765 9 -258430.11049 20622559.4574
38137558.783 335846.284 9
00 01 13 14 45 2.0000000 0 8G25G17G06G05G24G29G30S20 0.000535144

```

21839100.418	-240352.173 9	-187323.00449	21839101.6534
25150565.890	-168150.148 9	-131078.97647	25150576.2144
20531065.378	763136.116 9	594641.73549	20531066.8984
23002622.082	-427748.683 9	-333352.63648	23002625.3444
23610990.819	-381520.461 9	-297326.20848	23610995.8424
23955629.062	-145914.531 9	-113752.94748	23955636.5544
20622750.161	-330614.723 9	-257645.40149	20622751.0554
38137558.365	335843.457 9		

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

+-----+
|                                     |
|                               TABLE A18                               |
|                               GEO NAVIGATION MESSAGE FILE - EXAMPLE   |
+-----+

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

2.10	H: GEO NAV MSG DATA	RINEX VERSION / TYPE
SuP v. 1.4	TESTUSER 04-02-00 10:04	PGM / RUN BY / DATE
		COMMENT
The file contains navigation message data of the		COMMENT
geostationary AOR-E satellite (PRN 120 = S20)		COMMENT
		COMMENT
		END OF HEADER

20 00 01 13 14 46 24.0	.209547579288D-07	-.545696821064D-11	.532351280000D+05
.406131052800D+08	.150625000000D+01	.875000000000D-04	.000000000000D+00
-.112454290400D+08	.308125000000D+01	-.112500000000D-03	.400000000000D+01
.781616000000D+05	.959600000000D+01	-.437500000000D-03	.000000000000D+00
20 00 01 13 14 48 00.0	.204890966415D-07	-.545696821064D-11	.533161280000D+05
.406132503200D+08	.151500000000D+01	.875000000000D-04	.000000000000D+00
-.112451338400D+08	.307000000000D+01	-.125000000000D-03	.400000000000D+01
.790812000000D+05	.955600000000D+01	-.437500000000D-03	.000000000000D+00
20 00 01 13 14 49 36.0	.195577740669D-07	-.545696821064D-11	.533981280000D+05
.406133961600D+08	.152375000000D+01	.875000000000D-04	.000000000000D+00
-.112448396800D+08	.305875000000D+01	-.125000000000D-03	.400000000000D+01
.799968000000D+05	.951600000000D+01	-.437500000000D-03	.000000000000D+00
20 00 01 13 14 51 12.0	.190921127796D-07	-.545696821064D-11	.534791280000D+05
.406135428800D+08	.153250000000D+01	.875000000000D-04	.000000000000D+00
-.112445465600D+08	.304687500000D+01	-.125000000000D-03	.400000000000D+01
.809084000000D+05	.947600000000D+01	-.437500000000D-03	.000000000000D+00

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|