

## Formulae for bed density, water content and salt correction. (In cgs)

(I.N. McCave, Dept. Earth Sciences, Cambridge).

### Data

$$\begin{aligned} \text{weight wet (+sw)} &= x \text{ g} \\ \text{weight dry (+s)} &= y \text{ g} \\ (x-y) = \text{wt of water} &= \text{wt of sea water-wt of salt} = (sw-s) = (1-S)sw \end{aligned}$$

### Assumed

$$\begin{aligned} \text{sediment density } \rho_p &= 2.65 \text{ g/cm}^3 \text{ (if sed is not qtz make up density by proportion*)} \\ \text{salinity } S &= 35 \text{ g/kg} = 0.035 \\ \text{water density } \rho_w &= 1.025 \text{ g/cm}^3 \text{ (@ } 20^\circ\text{C)} \end{aligned}$$

### Derived

$$\begin{aligned} \text{dry mud weight less salt } Y &= (y-Sx)/(1-S) = (y-0.035x)/0.965 \\ \text{salt content} = (y-Y)/Y &= S(x-y)/(y-Sx) \\ \text{"water content" } W &= \text{wt of salt water/wt of wet sediment} \\ W &= 1.025 (x-y)/x \text{ (usually expressed as \%)} \\ \text{dry mud volume } V_m &= \frac{Y}{\rho_p} = [Y/2.65] \text{ cm}^3 \\ \text{fluid volume } V_w &= \frac{(x-Y)}{\rho_w} = [(x-Y)/1.025] \text{ cm}^3 \\ \therefore \text{ wet sample volume } V_t &= \left[ \frac{Y}{2.65} + \frac{(x-Y)}{1.025} \right] = \frac{2.65x - 1.625Y}{2.71625} \text{ cm}^3 \\ \text{porosity } P &= V_w/V_t = \varepsilon/(1+\varepsilon) \\ \text{dry bulk density} &= y/V_t \text{ g/cm}^3 \\ \text{Salt-corrected dry bulk density } \rho_d &= Y/V_t \text{ g/cm}^3 \\ \text{voids ratio } \varepsilon &= P/V_m = P/(1-P) \end{aligned}$$

If a dry lump of sediment is taken and carbon content  $C$  is measured and expressed as  $[C/\text{dried sed wt}]$ , it is wrong unless corrected for salt content: *it should be corrected to  $[C/\text{wt sed}]$  i.e. salt-corrected.*

$$1 \text{ cm of core} = Y/V_t \text{ g/cm}^2 \text{ of salt-free sed.}$$

with sedimentation rate  $SR$  cm/ka, and mass accumulation rate  $MAR$  g/cm<sup>2</sup>/ka

$$MAR = SR (Y/V_t) \text{ g/cm}^2/\text{ka}$$

Summary formulae:

$$\rho_d = \rho_s (1 - P)$$

$$\rho_t = \Delta\rho (1 - P) + \rho_w$$

$$\rho_t = \rho_d \Delta\rho$$

$$\rho_d = (\rho_t - \rho_w) \rho_s / \Delta\rho$$

$\rho_w$  = density of water,  $\rho_s$  = sediment grain density,  $\Delta\rho = (\rho_s - \rho_w)$ ,  $\rho_t$  = total wet bulk density  $\times V_t$ ,  
 $\rho_d$  = salt-corrected dry bulk density (concentration),  $P$  = porosity.

Worked example:

weight wet	=	10 g
weight dry	=	7 g
<b>Y</b>	=	$(7 - 0.035 \times 10) / 0.965 = \underline{6.891.g.}$
water content <b>W</b>	=	0.3075 or 30.8%
Salt content of dry mud + salt	=	0.0158 (a ratio)
dry mud vol <b>V<sub>m</sub></b>	=	$\frac{6.891}{2.65} = 2.600 \text{ cm}^3$
fluid vol <b>V<sub>w</sub></b>	=	$3.033 \text{ cm}^3$
wet sample vol <b>V<sub>t</sub></b>	=	$5.634 \text{ cm}^3$
porosity <b>P</b>	=	0.538
voids ratio $\epsilon$	=	1.16
dry bulk $\rho$	=	$1.243. \text{ g/cm}^3$
Salt-corr. dry bulk $\rho_d$	=	$1.223 \text{ g/cm}^3$
$\therefore$ 1 cm core	=	$1.223 \text{ g/cm}^2 \text{ dry sed.}$
$\therefore$ 5 cm/ka SR	=	$6.1 \text{ g/cm}^2/\text{ka dry sed MAR.}$

if say 9.1% by weight is C on a salt-free basis by wt., then MAR of C =  $0.56 \text{ g/cm}^2/\text{ka}$ .

To express  $\rho_d$  in terms of water content **W**

$$\rho_d = \frac{2.65 (1 - 1.011\mathbf{W})}{(1 + 1.603\mathbf{W})} \quad (\mathbf{W} \text{ was a fraction})$$

(with  $\mathbf{W} = 0.3075$  above gives  $\rho_d = 1.223 \text{ g/cm}^3$  as required).

\* 'by proportion' means, normally proportion of opal to (qtz+CO<sub>3</sub>),  $\rho_p = 2.1$  vs 2.65

## Formulae for bed density, water content and salt correction. (In SI)

(I.N. McCave, Dept. Earth Sciences, Cambridge).

### Data

$$\begin{aligned} \text{weight wet (+sw)} &= x \text{ kg} \\ \text{weight dry (+s)} &= y \text{ kg} \\ (x-y) = \text{wt of water} &= \text{wt of sea water-wt of salt} = (sw-s) = (1-S)sw \end{aligned}$$

### Assumed

$$\begin{aligned} \text{sediment density } \rho_p &= 2650 \text{ kg/m}^3 \\ \text{salinity } S &= 35 \text{ g/kg} = 0.035 \\ \text{seawater density } \rho_w &= 1025 \text{ kg/m}^3 \text{ (@ } 20^\circ\text{C)} \end{aligned}$$

### Derived

$$\begin{aligned} \text{dry mud weight less salt } Y &= (y-Sx)/(1-S) = (y-0.035x)/0.965 \\ \text{salt content } = (y-Y)/Y &= S(x-y)/(y-Sx) \\ \text{"water content" } W &= \text{wt of salt water/wt of wet sediment} \\ W &= 1025 (x-y)/x \text{ (usually expressed as \%)} \\ \text{dry mud volume } V_m &= \frac{Y}{\rho_p} = [Y/2650] \text{ m}^3 \\ \text{fluid volume } V_w &= \frac{(x-Y)}{\rho_w} = [(x-Y)/1025] \text{ m}^3 \\ \therefore \text{ wet sample volume } V_t &= \left[ \frac{Y}{2650} + \frac{(x-Y)}{1025} \right] = \frac{2650x - 1625Y}{2716.25} \text{ m}^3 \\ \text{porosity } P &= V_w/V_t = \varepsilon/(1+\varepsilon) \\ \text{dry bulk density} &= y/V_t \text{ kg/m}^3 \\ \text{Salt-corrected dry bulk density } \rho_d &= Y/V_t \text{ kg/m}^3 \\ \text{voids ratio } \varepsilon &= P/V_m = P/(1-P) \end{aligned}$$

If a dry lump of sediment is taken and carbon content  $C$  is measured and expressed as  $C/(\text{wt sed} + \text{salt})$ , it is wrong unless corrected for salt content: *it should be corrected to  $[C/\text{wt sed}]$ .*

$$1 \text{ cm of core} = 0.01Y/V_t \text{ kg/m}^2 \text{ of salt-free sed.}$$

with sedimentation rate  $SR$  m/ma (=mm/ka), and mass accumulation rate  $MAR$  kg/m<sup>2</sup>/Ma

$$MAR = SR (Y/V_t) \text{ kg/m}^2/\text{Ma}$$

Summary formulae:

$$\rho_d = \rho_s (1 - P)$$

$$\rho_t = \Delta\rho (1 - P) + \rho_w$$

$$\rho_t = \rho_d \Delta\rho$$

$$\rho_d = (\rho_t - \rho_w) \rho_s / \Delta\rho$$

$\rho_w$  = density of water,  $\rho_s$  = sediment grain density,  $\Delta\rho = (\rho_s - \rho_w)$ ,  $\rho_t$  = total wet bulk density  $\times V_t$ ,  
 $\rho_d$  = salt-corrected dry bulk density (concentration),  $P$  = porosity.

Worked example:

weight wet	=	$10 \times 10^{-3}$ kg
weight dry	=	$7 \times 10^{-3}$ kg
<b>Y</b>	=	$(7 - 0.035 \times 10) \times 10^{-3} / 0.965 = \underline{6.891 \times 10^{-3}}$ kg
water content <b>W</b>	=	0.3075 or 30.8%
Salt content of dry mud + salt	=	0.0158 (a ratio)
dry mud vol <b>V<sub>m</sub></b>	=	$\frac{6.891 \times 10^{-3}}{2650} = 2.600 \times 10^{-6}$ m <sup>3</sup>
fluid vol <b>V<sub>w</sub></b>	=	$3.033 \times 10^{-6}$ m <sup>3</sup>
wet sample vol <b>V<sub>t</sub></b>	=	$5.634 \times 10^{-6}$ m <sup>3</sup>
porosity <b>P</b>	=	0.538
voids ratio $\epsilon$	=	1.16
dry bulk $\rho$	=	1243 kg/m <sup>3</sup>
Salt-corr. dry bulk $\rho_d$	=	1223 kg/m <sup>3</sup>
$\therefore$ 1 cm core	=	12.23 kg/m <sup>2</sup> dry sed.
$\therefore$ 50 mm/ka SR	=	61.2 kg/m <sup>2</sup> /ma dry sed MAR.

if say 9.1% by weight is Carbon on a salt-free basis by wt., then MAR of C = 5.6 kg/m<sup>2</sup>/ma.

To express  $\rho_d$  in terms of water content **W**

$$\rho_d = \frac{2650 (1 - 1.011\mathbf{W})}{(1 + 1.603\mathbf{W})} \quad (\mathbf{W} \text{ was a fraction})$$

(with **W** = 0.3075 above gives  $\rho_d$  = 1223 kg/m<sup>3</sup> as required).