

# Master Track RV Polarstern ANT-XXIV/2

## Data Processing Report

### Contents

<b>1 Introduction</b>	<b>1</b>
<b>2 Workflow</b>	<b>1</b>
<b>3 Sensor Layout</b>	<b>2</b>
<b>4 Processing Report</b>	<b>3</b>

Contact:

Dr. Rainer Knust  
Alfred Wegener Institute  
Columbusstrasse, D-27568 Bremerhaven, GERMANY  
Tel: +49(471)4831-1709  
Fax: +49(471)4831-1918  
Mail: Polarstern-Coordination@awi.de

Processing Agency:

FIELAX  
Gesellschaft für wissenschaftliche Datenverarbeitung mbH  
Schleusenstr. 14, D-27568 Bremerhaven, GERMANY  
Tel: +49 (0) 471 30015 0  
Fax: +49 (0) 471 30015 22  
Mail: info@fielax.de

Ref.: ANT24_2_nav.pdf	Vers.: 1	Date: 2015/08/21	Status: final
-----------------------	----------	------------------	---------------

# 1 Introduction

This report describes the processing of raw data acquired by position sensors on board RV Polarstern during expedition ANT-XXIV/2 to receive a validated master track which is used as reference of further expedition data.

# 2 Workflow

The different steps of processing and validation are visualized in figure 1. Unvalidated data of up to three sensors and ship-motion data are extracted from the DAVIS SHIP data base (<https://dship.awi.de>) in a 1-second interval. They are converted to ESRI point shapefiles and imported to ArcGIS. A visual screening is performed to evaluate data quality and remove outliers manually. The position data from each position sensor are centered to the destined master track origin by applying ship-motion data (angles of roll, pitch and heading) and lever arms. For all three resulting position tracks, a quality check is performed using a ship's speed filter and an acceleration filter. Filtered positions are flagged. In addition, a manual check is performed to flag obvious outliers. Those position tracks are combined to a single master track depending on a sensor priority list (by accuracy, reliability) and availability / applied exclusion of automatically or manually flagged of data. Missing data up to a time span of 60 seconds are linearly interpolated. To reduce the amount of points for overview maps the master track is generalized by using the Ramer-Douglas-Peucker algorithm. This algorithm returns only the most significant points from the track. Full master track and generalized master track are written to text files and imported to PANGAEA (<http://www.pangaea.de>) for publication.



Figure 1: Workflow of master track data processing

### 3 Sensor Layout

This chapter describes the position sensors mounted during this cruise.

#### Cruise details

Vessel name	RV Polarstern
Cruise name	ANT-XXIV/2
Cruise start	28.11.2007 Cape Town
Cruise end	04.02.2008 Cape Town
Cruise duration	69 days
Master track reference point:	Resulting master track is referenced to <i>MINS installation point</i> .

#### Position sensors

Sensor name	<b>Raytheon Anschuetz MINS2</b> , short: MINS
Description	Marine inertial navigation system with reference positions from Trimble DGPS
Accuracy	< 60 m CEP50 (with SPS GPS)
Installation point	Gravimeter room on F-Deck, close to COG
Installation offset	Offset from master track reference point to sensor installation point X Positive to bow 0.000 m Y Positive to starboard 0.000 m Z Positive upwards 0.000 m

Sensor name	<b>Trimble Marine SPS461 (1)</b> , short: Trimble 1
Description	DGPS-Receiver, correction type DGPS RTCM 2.x, correction source DGPS Base via radio
Accuracy	Horizontal: $\pm 0.25$ m + 1 ppm & Vertical: $\pm 0.50$ m + 1 ppm
Installation point	Observation deck (starboard)
Installation offset	Offset from master track reference point to sensor installation point X Positive to bow 22.777 m Y Positive to starboard -5.460 m Z Positive upwards 21.525 m

Sensor name	<b>Trimble Marine SPS461 (2)</b> , short: Trimble 2
Description	DGPS-Receiver, correction type DGPS RTCM 2.x, correction source DGPS Base via radio
Accuracy	Horizontal: $\pm 0.25$ m + 1 ppm & Vertical: $\pm 0.50$ m + 1 ppm
Installation point	Observation deck (port)
Installation offset	Offset from master track reference point to sensor installation point X Positive to bow 16.527 m Y Positive to starboard 12.408 m Z Positive upwards 21.538 m

### Motion sensor

Sensor name	<b>Raytheon Anschuetz MINS2</b> , short: MINS
Description	Marine inertial navigation system with reference positions from Trimble DGPS
Accuracy	$\pm 0.02^\circ$ roll, $\pm 0.02^\circ$ pitch, $\pm 0.05^\circ$ heading
Installation point	Gravimeter room on F-Deck, close to COG

## 4 Processing Report

### Database Extraction

Data source	DSHIP database (dship.awi.de)
Exported values	7776000
First dataset	2007-11-28T00:00:00 UTC
Last dataset	2008-02-04T23:59:59 UTC

### Centering & Motion Compensation

Each position track has been centered to the *MINS installation point* by applying the correspondent motion angles for heading, roll and pitch as well as the installation offsets from chapter 2. The motion data were acquired by Raytheon Anschuetz MINS2.

### Automatic Validation

The following thresholds were applied for the automatic flagging of the position data:

Speed	Maximum 20 kn between two datapoints.
Acceleration	Maximum $1 \text{ m/s}^2$ between two datapoints.
Change of course	Maximum $5^\circ$ between two datapoints.

## Manual Validation

Obvious outliers were removed manually. For details see Processing Logbook of RV Polarstern (<hdl:10013/epic.45909>).

## Flagging result

	MINS		Trimble 1		Trimble 2	
Missing	20640	0.265%	16287	0.209%	16390	0.211%
Speed	6174	0.079%	1698	0.022%	5026	0.065%
Acceleration	62501	0.804%	54133	0.696%	162652	2.092%
Course	2006104	25.799%	1872701	24.083%	2387428	30.703%
Manually	1975	0.025%	4275	0.055%	20004	0.257%

## Master Track Generation

The master track is derived from the position sensors' data selected by priority.

Sensor priority used:

1. MINS
2. Trimble 1
3. Trimble 2

Filters applied: manual, speed, acceleration, course.

Distribution of position sensor data in master track:

Sensor	Data points	Percentage
Total	5961600	76.667 %
MINS	4302847	72.176 %
Trimble 1	524044	8.790 %
Trimble 2	299999	5.032 %
Interpolated	826548	13.865 %
Gaps	8162	0.137 %

## Remarks

None.

## Score

For each cruise, a score is calculated ranging from 0 (no data) to 100 (only very good data). the score for the cruise ANT-XXIV/2 is 86.

## Generalization

The master track is generalized to receive a reduced set of the most significant positions of the track using the Ramer-Douglas-Peucker algorithm and allow a maximum tolerated distance between points and generalized line of 4 arcseconds.

Results:

Number of generalized points	4932 points
Data reduction	99.9173 %

## Result files

### Report in XML format:

The XML contains all information of the master track generation in a machine-readable format. In addition a XSD schema file is provided.

### Master track text file:

The format is a plain text (tab-delimited values) file with one data row in 1 second interval.

Column separator	Tabulator "\t"	
Column 1	Date and time expressed according to ISO 8601	
Column 3	Latitude in decimal format, unit degree	
Column 4	Longitude in decimal format, unit degree	
Column 5	Flag for data source	
	1	MINS
	2	Trimble 1
	3	Trimble 2
	INTERP	Interpolated point
	GAP	Missing data

### Text file of the generalized master track:

The format is a plain text (tab-delimited values) file.

Column separator	Tabulator "\t"
Column 1	Date and time expressed according to ISO 8601
Column 2	Latitude in decimal format, unit degree
Column 3	Longitude in decimal format, unit degree

### Processing Report:

This PDF document.

### Cruise map




Figure 2: Map of the generalized master track